air Go live reload

File change watched ext/dir → delay → **build.cmd** go build -o ./tmp/main . → stop old, start → **entrypoint** your app → proxy → **Browser** reloads

CONCEPTS

air watches your files, runs the build command on each change, then restarts the built binary. It reads .air.toml in the current directory and uses defaults without one.

Air's own flags come first; everything after -- goes to your program.

INSTALL

`go install github.com/air-verse/air@latest`
Install into GOPATH/bin

`export PATH=$PATH:$(go env GOPATH)/bin`
Fix 'command not found: air'

`go get -tool github.com/air-verse/air@latest`
Add as a project-local tool

`go tool air -v`
Run the project-local air

`brew install go-air`
Install with Homebrew

RUN

`air init`
Create .air.toml with defaults

`air`
Run with .air.toml or defaults

RUN (cont.)

`air -c <file>`
Use a specific config file

`air -d`
Debug mode, print all logs

`air -v`
Print the version

`air -h`
List every flag

`air server --port 8080`
Run the binary with these args

`air -c <file> -- -h`
Split air's flags from the app's

FLAG OVERRIDES

`air --build.cmd "go build -o ./tmp/main ./cmd/api"`
Set the build command

`air --build.entrypoint ./tmp/main`
Set the binary to run

`air --build.exclude_dir node_modules,vendor`
Exclude dirs (comma list)

`air --build.include_ext go,html`
Watch these extensions

FLAG OVERRIDES (cont.)

`air --build.delay 500`
Debounce rebuilds (ms)

[BUILD] SETTINGS

`cmd = "go build -o ./tmp/main ."`
Command that builds the app

`entrypoint = ["./tmp/main"]`
Executable plus default args

`args_bin = ["-v"]`
Extra args for the binary

`include_ext = ["go", "tpl", "html"]`
Extensions to watch

`exclude_dir = ["tmp", "vendor"]`
Directories to ignore

`include_dir = ["cmd", "internal"]`
Only watch these dirs

`exclude_regex = ["_test\.go"]`
Ignore paths by regex

`delay = 1000`
Debounce before rebuild (ms)

`stop_on_error = true`
Stop old binary if build fails

[BUILD] SETTINGS (cont.)

`send_interrupt = true`
Interrupt before killing the app

`poll = true`
Poll instead of fsnotify

`pre_cmd = ["go generate ./..."]`
Commands before each build

TOP-LEVEL & MISC

`root = "."`
Working directory to watch

`tmp_dir = "tmp"`
Folder for build output and logs

`env_files = [".env"]`
Load .env files; later wins

BROWSER RELOAD & RULES

`[proxy] enabled = true`
Reload the browser after rebuilds

`proxy_port = 8090`
Port you open in the browser

`app_port = 8080`
Port your app listens on

BROWSER RELOAD & RULES (cont.)

The proxy injects its script before </body>; HTML without it is served unchanged. Static assets must match include_dir, include_ext or include_file.

`[[build.rules]]`
Run a command instead of a rebuild

DOCKER

`docker run -it --rm -w /app -v $(pwd):/app -p 8080:8080 cosmtrek/air`
Run the official image

RECIPES

Web app with browser reload

```
air init
# edit .air.toml:
#   [build] include_ext = ["go", "html", "css"]
#   [proxy] enabled = true, proxy_port = 8090, app_port = 8080
air
# open http://localhost:8090
```

Several mains, one config

```
air --build.cmd "go build -o ./tmp/api ./cmd/api" \
    --build.entrypoint ./tmp/api
```