Ansible IT automation

Inventory hosts and groups → *pattern* → **Playbook** plays and tasks → *SSH* → **Modules** run on targets → *result* → **Report** ok / changed / failed

CONCEPTS

> Ansible connects over SSH and needs no agent. Playbooks describe a desired state, so running one twice should change nothing the second time.

> Prefer modules over raw shell: they report changed correctly and are idempotent.

AD-HOC

`ansible all -m ping`
Test connection and Python on hosts

`ansible <pattern> -m command -a "<cmd>"`
Run one command on hosts

`ansible <pattern> -m shell -a "<cmd>"`
Run through a shell

`ansible <pattern> -b -m apt -a "name=<pkg> state=present"`
Install a package as root

`ansible <pattern> -m setup`
Gather facts

`ansible <pattern> -m copy -a "src=<f> dest=<path>"`
Copy a file to hosts

AD-HOC (cont.)

`ansible <pattern> -m service -a "name=<svc> state=restarted"`
Restart a service

`ansible <pattern> --list-hosts`
Show which hosts match

PLAYBOOKS

`ansible-playbook <file>`
Run a playbook

`ansible-playbook <file> -i <inventory>`
Use a specific inventory

`ansible-playbook <file> --check`
Dry run, change nothing

`ansible-playbook <file> --diff`
Show file changes

`ansible-playbook <file> --syntax-check`
Parse only

`ansible-playbook <file> --list-tasks`
List tasks that would run

`ansible-playbook <file> --list-hosts`
List targeted hosts

`ansible-playbook <file> --start-at-task "<name>"`
Resume at a task

TARGETING & VARIABLES

`-l <pattern>` / `--limit <pattern>`
Restrict to hosts or groups

`-t <tag>` / `--tags <tag>`
Run only tagged tasks

`--skip-tags <tag>`
Skip tagged tasks

`-e <key>=<value>`
Set an extra variable

`-e @<file>`
Load variables from a file

`-v` / `-vvv`
More output detail

`--ask-vault-pass`
Prompt for the vault password

PRIVILEGES & CONNECTION

`-b` / `--become`
Escalate privileges

`-K` / `--ask-become-pass`
Prompt for the sudo password

`-u <user>`
Remote login user

`--private-key <file>`
SSH key to use

INVENTORY

`ansible-inventory --graph`
Tree of groups and hosts

`ansible-inventory --list`
Full inventory as JSON

`ansible-inventory --host <host>`
Variables of one host

Variable precedence (low to high)

Source	Wins over
role defaults	nothing
inventory vars	defaults
play vars	inventory
extra vars (-e)	everything

VAULT

`ansible-vault create <file>`
New encrypted file

`ansible-vault encrypt <file>`
Encrypt an existing file

`ansible-vault edit <file>`
Edit an encrypted file

`ansible-vault view <file>`
Show decrypted content

`--vault-password-file <file>`
Read the password from a file

GALAXY

`ansible-galaxy collection install <ns.name>`
Install a collection

`ansible-galaxy collection install -r requirements.yml`
Install from a requirements file

`ansible-galaxy collection list`
Installed collections

`ansible-galaxy role install <name>`
Install a role

`ansible-galaxy role install -r requirements.yml`
Install roles from a file

`ansible-galaxy role init <name>`
Scaffold a new role

DOCS & CONFIG

`ansible-doc <module>`
Module documentation

`ansible-doc -s <module>`
Short snippet of a module

`ansible-config dump --only-changed`
Settings differing from defaults