Apache Ant Java build tool

CONCEPTS

Ant reads build.xml in the current directory. Run with no target and it runs the project's default target.

Project build.xml, default target
- **Target** named step, depends on others
  - **Task** javac, jar, copy ...

Properties are immutable: the first definition wins, so -D on the command line overrides build.xml.

depends only orders targets. It does not rerun a target that already ran in this invocation.

RUN

ant
Run the project's default target

ant *<target>* **[***<target>***...]**
Run targets in order

ant -projecthelp / ant -p
List targets that have a description

ant -buildfile *<file>* **/ ant -f** *<file>*
Use a different build file

ant -find [*<file>***] / ant -s [***<file>***]**
Search parent dirs for the build file

ant -version
Print Ant version

ant -diagnostics
Print Java, classpath and Ant diagnostics

ant -help / ant -h
Show command line options

ant -keep-going / ant -k
Continue with targets not depending on a failure

ant -noinput
Never prompt for input (CI)

PROPERTIES AND OUTPUT

ant -D*<name>***=***<value>*
Set a property from the command line

ant -propertyfile *<file>*
Load properties from a file

ant -quiet / ant -q
Less output

ant -silent / ant -S
Only task output and failures

ant -verbose / ant -v
Extra output

ant -debug / ant -d
Debugging output

ant -logfile *<file>* **/ ant -l** *<file>*
Write the log to a file

ant -lib *<path>*
Add jars or dirs to Ant's classpath

ANT_OPTS="-Xmx1g" ant
Pass options to the JVM

BUILD FILE BASICS

<project name="<n>"
default="*<target>***"**
basedir=".">
Root element

<target name="<n>"
depends="*<a>***,***<b>***"**
description="*<text>***">**
Define a target

<property name="<n>"
value="*<v>***"/>**
Define a property

<property file="build.properties"/>
Load properties from a file

<property environment="env"/>
Read env vars as ${env.NAME}

${*<name>***}**
Reference a property

${basedir}
Project base directory

<target name="<n>"
if="*<prop>***">**
Run only if a property is set

BUILD FILE BASICS (cont.)

<target name="<n>"
unless="*<prop>***">**
Run only if a property is not set

*<import file="<other.xml>"***/>**
Include another build file

*<path id="<id>">**<fileset dir="lib" includes="*.jar"/></path>***
Reusable classpath

<fileset dir="<d>"
includes="/*.java"**
excludes="*<pat>***"/>**
Select files by pattern

*<echo message="<text>"***/>**
Print a message

*<exec executable="<cmd>">**<arg value="<a>"***/>**</exec>***
Run an external command

COMMON TASKS

*<mkdir dir="<d>"***/>**
Create a directory

*<delete dir="<d>"***/>**
Remove a directory tree

*<copy todir="<d>">**<fileset dir="<s>"***/>**</copy>***
Copy files

<move file="<f>"
tofile="*<t>***"/>**
Move or rename a file

<javac srcdir="src" destdir="build/classes" classpathref="<id>"
includeantruntime="false"/>
Compile Java sources

*<jar destfile="dist/<n>***.jar"**
basedir="build/classes"/>
Build a jar

*<manifest>**<attribute name="Main-Class" value="<cls>"***/>**</manifest>***
Set jar manifest (inside <jar>)

<java classname="<cls>"
classpathref="*<id>***"**
fork="true"/>
Run a Java class

<junit printsummary="yes" haltonfailure="yes">
Run JUnit tests