autossh Self-healing ssh tunnels

START HERE

autossh -M 0 *<ssh args>*
Restart ssh, no monitor port

AUTOSSH_GATETIME=0 autossh ...
Keep retrying at boot

autossh -M 0 -N -L *<lport>*:*<dst>*:*<dport>* *<host>*
Persistent local forward

kill -USR1 *<pid>*
Force a new ssh now

autossh -M 0 -f -N -R *<rp>*:**localhost:***<p>* *<host>*
Background reverse tunnel

-o ServerAliveInterval=30 -o ServerAliveCountMax=3
Detect a dead link

-o ExitOnForwardFailure=yes
Retry if a forward fails

autossh -M *<port>* *<host>*
Monitor via port and port+1

autossh supervisor → **spawns** → **ssh** your tunnel or session → **keepalive or test data** → **Remote host** sshd → **ssh exits or stalls** → **Restart** backs off up to the poll time

CONCEPTS

autossh runs ssh for you: every argument except its own flags goes to ssh unchanged. Get the plain ssh command working first, then put autossh in front.

Use key or agent login: autossh cannot answer a password prompt, and -f makes that impossible.

RUNNING AUTOSSH

autossh -M 0 *<host>*
Supervised login session

A normal exit (typing exit) ends autossh too; only failures restart ssh.

autossh -M 0 -N -L *<lport>*:*<dst>*:*<dport>* *<host>*
Keep a local forward alive

autossh -M 0 -N -R *<rp>*:**localhost:***<p>* *<host>*
Keep a reverse tunnel alive

autossh -M 0 -N -D *<port>* *<host>*
Keep a SOCKS proxy alive

autossh -M 0 -f -N *<ssh args>*
Drop to the background

-f is autossh's own: ssh cannot then ask for passwords or passphrases.

RUNNING AUTOSSH (cont.)

autossh -M 0 -N -J *<jump>* *<host>*
Supervise a tunnel via a jump host

autossh -M 0 -i *<key>* **-p** *<port>* *<user>*@*<host>*
Choose key and port as for ssh

Prefer an entry in ~/.ssh/config for the forwards and keepalives, then run just autossh -M 0 -f -N <host>.

MONITORING

-M 0
Disable the monitor port, rely on ssh keepalives

Needs ServerAliveInterval/ServerAliveCountMax so ssh exits when the link dies.

-M *<port>*
Monitor with a port pair

Uses <port> and <port>+1 locally and on the remote; both must be free.

-M *<port>*:*<echo_port>*
Monitor via a remote echo service

Port 7 is the inetd echo service, often disabled.

-o ServerAliveInterval=30 -o ServerAliveCountMax=3
Ssh quits after ~90 s of silence

MONITORING (cont.)

-o ExitOnForwardFailure=yes
Exit ssh if a forward cannot bind

-o ConnectTimeout=10
Fail fast when the host is down

-o BatchMode=yes
Never prompt: fail instead

On the server side ClientAliveInterval in sshd_config closes stale listening sockets when the client vanishes, so a restarted reverse tunnel can bind again.

ENVIRONMENT VARIABLES

AUTOSSH_GATETIME=*<s>*
Seconds ssh must survive to count as started (30)

0 disables the gate and retries even if the first ssh fails with status 1. Useful at boot.

AUTOSSH_POLL=*<s>*
Seconds between connection tests (600)

AUTOSSH_PORT=*<port>*
Monitor port; overrides -M

AUTOSSH_DEBUG=1
Debug log, copied to stderr

ENVIRONMENT VARIABLES (cont.)

AUTOSSH_LOGLEVEL=*<0-7>*
Syslog level, 7 chattiest

AUTOSSH_LOGFILE=*<file>*
Log to a file instead of syslog

AUTOSSH_PIDFILE=*<file>*
Write the autossh pid

Variables go in front of the command (AUTOSSH_GATETIME=0 autossh ...) or in a systemd Environment= line.

CONTROL AND TROUBLESHOOTING

kill -USR1 *<pid>*
Kill ssh and start a new one

kill -HUP *<pid>*
Prod autossh to retry now after back-off

kill *<pid>*
Stop autossh and its ssh child

SIGTERM, SIGINT and SIGKILL are treated as deliberate.

pgrep -af autossh
Find running autossh processes

AUTOSSH_DEBUG=1 autossh -M 0 -v *<ssh args>*
Debug autossh and ssh together

CONTROL AND TROUBLESHOOTING (cont.)

ss -tlnp | grep *<port>*
Check that the tunnel port is listening

If autossh exits at once, ssh failed in the first 30 s (gate time) or with status 1: run the ssh command alone to see the error.

Repeated quick failures make autossh back off, up to the poll time (10 minutes by default).

SERVICES

systemd unit

```
[Unit]
Description=Tunnel to <host>
After=network-online.target
Wants=network-online.target

[Service]
User=<user>
Environment=AUTOSSH_GATETIME=0
ExecStart=/usr/bin/autossh -M 0
-N \
  -o ServerAliveInterval=30 -o
ServerAliveCountMax=3 \
  -o ExitOnForwardFailure=yes \
  -L <lport>:localhost:<dport>
<host>
Restart=on-failure
RestartSec=10

[Install]
WantedBy=multi-user.target
```

SERVICES (cont.)

systemctl enable --now autossh-*<name>*
Start the unit now and at boot

journalctl -u autossh-*<name>* **-f**
Follow the unit's log

@reboot AUTOSSH_GATETIME=0 autossh -M 0 -f -N *<host>*
Crontab line to start at boot

Under systemd do not use -f: stay in the foreground so systemd can supervise the process.

Run the unit as a normal user with a passphrase-less key restricted on the server (command=, permitopen=).

RECIPES

Reach a remote database

```
autossh -M 0 -f -N \
  -o ServerAliveInterval=30 -o
ServerAliveCountMax=3 \
  -o ExitOnForwardFailure=yes \
  -L 5432:localhost:5432
<user>@<host>
psql -h localhost -p 5432
```

Persistent SOCKS proxy

```
autossh -M 0 -f -N -D 1080 \
  -o ServerAliveInterval=30 -o
ServerAliveCountMax=3 <host>
curl --socks5-hostname
localhost:1080 <url>
```