bluetoothctl Bluetooth from the shell

CONCEPTS

> <dev> is the device MAC address (AA:BB:CC:DD:EE:FF). Press Tab to complete it from the scan results.

Scan find it
↓ pair
Pair exchange keys
↓ trust
Trust allow reconnect
↓ connect
Connect use profiles

> Pairing needs an agent. Inside the prompt it is registered for you; in one-shot mode it is not, so pair interactively.

SESSION

bluetoothctl
Open the interactive prompt

bluetoothctl *<command>*
Run one command and exit

bluetoothctl --timeout *<seconds>* **scan on**
Scan for a fixed time, then exit

help
List the commands of this menu

quit
Leave the prompt

menu *<name>*
Enter a submenu

back
Return to the main menu

CONTROLLER

power on
Switch the adapter on

power off
Switch the adapter off

show
Show controller state

CONTROLLER (cont.)

list
List controllers

discoverable on
Let other devices find this one

pairable on
Accept incoming pairing requests

agent on
Register the pairing agent

default-agent
Make this agent the default

DISCOVER

scan on
Start scanning for devices

scan off
Stop scanning

scan le
Scan for Low Energy devices only

devices
List known devices

devices Paired
List only paired devices

devices Connected
List only connected devices

info *<dev>*
Show a device's state and profiles

PAIR AND CONNECT

pair *<dev>*
Pair with a device

trust *<dev>*
Let it reconnect automatically

connect *<dev>*
Connect all profiles

disconnect *<dev>*
Drop the connection

remove *<dev>*
Forget the device and its pairing