BorgBackup Deduplicating backups

CONCEPTS

> Set BORG_REPO and BORG_PASSCOMMAND once; then use :: instead of the repo path (borg create ::<archive> <path>).

Files your data
↓ create
Archive deduplicated, encrypted
↓ prune
Deleted archive space still used
↓ compact
Space freed repo shrinks

> Lose the key or passphrase and the data is gone. Keep a key export and the passphrase outside the repo and the backed-up machine.

REPOSITORY

`borg init -e <mode> <repo>`
Create a repository

`export BORG_REPO=<repo>`
Default repository

`export BORG_PASSCOMMAND="<cmd>"`
Get the passphrase from a command

`ssh://<user>@<host>:<port>/<path>`
Remote repository URL

`borg key export <repo> <file>`
Back up the key

CREATE

`borg create <repo>::<archive> <path>...`
Back up paths into a new archive

`borg create --stats --progress <repo>::<archive> <path>`
Show statistics and progress

`borg create --list --dry-run <repo>::<archive> <path>`
Preview what would be stored

CREATE (cont.)

`borg create ... <repo>::{hostname}-{now:%Y-%m-%d} <path>`
Name archives by host and date

`borg create -e '<pattern>' ...`
Exclude matching paths

BROWSE AND RESTORE

`borg list <repo>`
List archives

`borg list <repo>::<archive>`
List files of an archive

`borg extract <repo>::<archive>`
Restore everything into current dir

`borg extract <repo>::<archive> <path>`
Restore only one path

`borg mount <repo>::<archive> <dir>`
Mount an archive via FUSE

`borg umount <dir>`
Unmount

RETENTION AND UPKEEP

`borg prune -v --list --dry-run <keep-options> <repo>`
Preview pruning

`borg prune --keep-daily 7 --keep-weekly 4 --keep-monthly 6 <repo>`
Apply a retention policy

`borg prune -a '{hostname}-*' ... <repo>`
Only touch one host's archives

`borg compact <repo>`
Free space after prune/delete

`borg check <repo>`
Verify repo and archive consistency

COMMON OPTIONS

`-v / --info`
More output