Homebrew Package manager

CONCEPTS

A formula is a command-line package built or poured from a bottle; a cask is a prebuilt GUI app or binary (macOS mostly).

Taps homebrew-core, cask
↓ `brew update`
Formula or cask recipe
↓ `brew install`
Cellar versioned files
↓ `link`
Prefix bin on your PATH

install and upgrade usually run update first, so a fresh brew update is rarely needed before them.

INSTALL AND REMOVE

`brew install <formula>`
Install a command-line package

`brew install --cask <cask>`
Install a GUI app

`brew uninstall <name>`
Remove a package

`brew reinstall <name>`
Remove and install again

`brew install -n <name>`
Dry run, change nothing

UPDATE AND UPGRADE

`brew update`
Fetch latest formulae and casks

`brew outdated`
List packages with newer versions

`brew upgrade`
Upgrade all outdated packages

`brew upgrade <name>`
Upgrade one package

`brew upgrade -n`
Preview what would upgrade

UPDATE AND UPGRADE (cont.)

`brew upgrade --cask --greedy`
Include casks that self-update

SEARCH AND INSPECT

`brew search <text>`
Search formulae and casks

`brew info <name>`
Version, deps, caveats, install state

`brew list`
List installed formulae and casks

`brew leaves`
Packages you installed directly

SERVICES

`brew services list`
Services and their status

`brew services start <formula>`
Run now and at login/boot

`brew services stop <formula>`
Stop and unregister

TAPS

`brew tap <user>/<repo>`
Add a third-party repository

CLEANUP AND DOCTOR

`brew cleanup`
Delete old versions and stale downloads

`brew autoremove`
Remove unneeded dependencies

`brew doctor`
Diagnose common problems

BREWFILE (BUNDLE)

`brew bundle dump`
Write installed state to Brewfile

`brew bundle`
Install everything in the Brewfile