broot Tree navigator

CONCEPTS

> Run broot through the br function, not the binary: only then can Alt+Enter change your shell's directory.

LAUNCH

`br`
Start broot in the current directory

`br` *`<path>`*
Start in another directory, or preview a file

`br -s`
Show sizes

`br -h`
Show hidden files

`br -i`
Show git-ignored files

`br -sdp`
Use as an ls replacement

`br -w`
Whale mode: find what eats disk space

`broot --install`
(Re)install the br shell function

NAVIGATE

`Arrows`
Move the selection

`Enter`
Open file / make directory the root

`Alt+Enter`
Leave broot, cd the shell to the directory

`Esc`
Clear input / return to previous state / quit

`?`
Show help and config file location

`Ctrl+q`
Quit

`Alt+h`
Toggle hidden files

NAVIGATE (cont.)

`Alt+i`
Toggle git-ignored files

SEARCH

`<letters>`
Fuzzy match on sub-path from the root

`/`*`<regex>`*
Regex on file name

`c/`*`<text>`*
Files containing text

VIEW

`:size`
Toggle sizes

`:gs`
Show only files git sees as changed

FILES

`:e`
Edit file in your editor

`:cp` *`<path>`*
Copy the selection

`:mv` *`<path>`*
Move the selection

`:rm`
Delete the selection

`:rename`
Rename (F2), pre-filled with current name

`:md` *`<name>`*
Create a directory (slashes allowed)

PANELS AND STAGING

`Ctrl+Right`
Open or focus the panel on the right

`:cpp`
Copy selection to the other panel

`Ctrl+g`
Stage or unstage the selection