buf Protobuf toolkit

START HERE

`buf` **`config init`**
Create buf.yaml

`buf` **`dep update`**
Pin dependencies

`buf` **`build`**
Compile and check protos

`buf` **`curl`** *`<url>`*
Call an RPC

`buf` **`lint`**
Check style rules

`buf` **`format -w`**
Format files in place

`buf` **`breaking --against`** *`<input>`*
Detect breaking changes

`buf` **`generate`**
Generate code

proto files buf.yaml module → `buf lint / format` → **Checked source** style ok → `buf breaking` → **Compatible** vs. last release → `buf generate` → **Generated code** buf.gen.yaml

CONCEPTS

buf reads buf.yaml for modules, lint and breaking rules, and buf.gen.yaml for code generation. Inputs default to the current directory.

An input can be a directory, a git ref, a tarball, an image file or a BSR module: the same argument works for build, lint, breaking and generate.

SETUP AND CONFIG

`buf` **`--version`**
Print the installed version

`buf` **`config init`**
Create a buf.yaml here

`buf` **`config ls-lint-rules`**
List available lint rules

`buf` **`config ls-breaking-rules`**
List available breaking rules

`buf` **`config ls-modules`**
List modules in the workspace

`buf` *`<command>`* **`--help`**
Help for any command

BUILD

`buf` **`build`**
Compile all protos in the module
Fails with the same errors protoc would report; a quick sanity check in CI.

BUILD (cont.)

`buf` **`build -o image.binpb`**
Write a binary image

`buf` **`build --as-file-descriptor-set -o fds.binpb`**
Write a plain FileDescriptorSet

`buf` **`build --path`** *`<dir/file.proto>`*
Build only part of the module

LINT

`buf` **`lint`**
Lint the current module

`buf` **`lint`** *`<input>`*
Lint a dir, git ref or image

`buf` **`lint --path`** *`<file.proto>`*
Lint selected files only

`buf` **`lint --exclude-path`** *`<path>`*
Skip files or directories

`buf` **`lint --error-format github-actions`**
Annotations for GitHub Actions

`// buf:lint:ignore` *`<RULE_ID>`*
Silence one rule above a line
Place it directly before the element; disallow_comment_ignores: true turns it off.

FORMAT

`buf` **`format`**
Print formatted files to stdout

FORMAT (cont.)

`buf` **`format -w`**
Rewrite files in place

`buf` **`format -d`**
Show a diff instead

`buf` **`format -d --exit-code`**
Fail if anything is unformatted (CI)

BREAKING CHANGES

`buf` **`breaking --against '.git#branch=main'`**
Compare with main in git

`buf` **`breaking --against`** *`<dir>`*
Compare with another directory

`buf` **`breaking --against image.binpb`**
Compare with a saved image

`buf` **`breaking --against`** *`<input>`* **`--path`** *`<dir>`*
Check only part of the module

`buf` **`breaking --against`** *`<input>`* **`--error-format github-actions`**
Annotations for CI

Breaking categories

Category	Catches changes that break
`FILE`	Generated source per file (default)
`PACKAGE`	Generated source per package
`WIRE_JSON`	Wire and JSON encoding
`WIRE`	Wire encoding only

BREAKING CHANGES (cont.)

`buf` **`build -o baseline.binpb`**
Save a baseline image of a release

GENERATE

`buf` **`generate`**
Run plugins from buf.gen.yaml

`buf` **`generate --template`** *`<file.yaml>`*
Use another template file

`buf` **`generate --path`** *`<dir>`*
Generate for part of the module

`buf` **`generate --include-imports`**
Also generate code for imports
Well-known types are not included.

`buf` **`generate --clean`**
Delete plugin output dirs first

`buf` **`generate`** *`<input>`*
Generate from a git repo or module

DEPENDENCIES AND MODULES

`buf` **`dep update`**
Resolve deps and write buf.lock

`buf` **`export`** *`<input>`* **`-o`** *`<dir>`*
Copy protos and deps into a dir

CONVERT AND CALL

`buf` **`convert`** *`<input>`* **`--type`** *`<pkg.Msg>`* **`--from`** *`<file>`***`.json --to`** *`<file>`***`.binpb`**
Convert a message between formats

`buf` **`curl --list-services`** *`<url>`*
List services via reflection

`buf` **`curl --list-methods`** *`<url>`*
List methods via reflection

`buf` **`curl -d '`***`<json>`***`'`** *`<url>/<pkg.Svc>/<Method>`*
Call an RPC with a JSON body

`buf` **`curl -d @`***`<file>`***`.json`** *`<url>/<pkg.Svc>/<Method>`*
Read the body from a file

`buf` **`curl --schema`** *`<dir>`* *`<url>/<pkg.Svc>/<Method>`*
Use local protos, no reflection

`buf` **`curl --protocol grpc`** *`<url>/<pkg.Svc>/<Method>`*
Speak gRPC (default is Connect)

`buf` **`curl -H "Authorization: Bearer`** *`<token>`***`"`** *`<url>/<pkg.Svc>/<Method>`*
Send a header

`buf` **`curl --http2-prior-knowledge`** *`<url>/<pkg.Svc>/<Method>`*
Plaintext HTTP/2 (h2c)

CONFIG FILES

buf.yaml

```
version: v2
modules:
  - path: proto
deps:
  - buf.build/googleapis/
googleapis
lint:
  use:
    - STANDARD
  except:
    - PACKAGE_VERSION_SUFFIX
breaking:
  use:
    - FILE
```

buf.gen.yaml

```
version: v2
clean: true
plugins:
  - remote: buf.build/
protocolbuffers/go
    out: gen/go
    opt: paths=source_relative
  - local: protoc-gen-go-grpc
    out: gen/go
inputs:
  - directory: proto
```

RECIPES

CI checks

```
buf format -d --exit-code
buf lint
buf build
buf breaking --against
'.git#branch=main'
```

Fresh code generation

```
buf dep update
buf generate --clean
git diff --exit-code gen/
```