Bundler Ruby dependencies

CONCEPTS

Commit Gemfile and Gemfile.lock. The Gemfile holds your constraints, the lockfile pins the exact versions everyone gets.

Gemfile your constraints
↓ install / update
Gemfile.lock exact versions
↓ install
Installed gems system or vendor/bundle
↓ exec / setup
Your app load path set

PROJECT

bundle init
Write a starter Gemfile here

bundle gem *<name>*
Scaffold a new gem

INSTALL & REMOVE

bundle install
Install gems, write Gemfile.lock

bundle add *<gem>*
Add a gem to the Gemfile and install

bundle add *<gem>* **-v "~> 1.2" -g development**
Add with version and group

bundle remove *<gem>*
Remove a gem from the Gemfile

RUN

bundle exec *<cmd>*
Run a command with the bundle's gems

bundle exec rake *<task>*
Run a Rake task in the bundle

UPDATE & OUTDATED

bundle update *<gem>*
Upgrade one gem and what it needs

bundle update --all
Upgrade everything

bundle outdated
List gems with newer versions

bundle update --patch
Prefer patch releases only

INSPECT

bundle list
Every gem in the bundle with version

bundle info *<gem>*
Details about one gem

bundle info *<gem>* **--path**
Where a gem is installed

LOCKFILE

bundle lock
Resolve and write the lockfile only

bundle lock --add-platform *<platform>*
Add a platform to the lockfile

CONFIG & DEPLOY

bundle config set --local *<name>* *<value>*
Set for this project

bundle config set --local path vendor/bundle
Install gems into the project

bundle config set --local deployment true
Frozen lockfile + vendor/bundle

bundle config set --local frozen true
Fail if the lockfile would change

bundle config set --local without 'development test'
Skip groups on install

GEMFILE SYNTAX

source "https://rubygems.org"
Where gems come from

gem "*<name>***"**
Depend on a gem

gem "*<name>***", "~> 1.2"**
Pessimistic: >= 1.2, < 2.0

gem "*<name>***", "~> 1.2.3"**
Pessimistic: >= 1.2.3, < 1.3

gem "*<name>***", group: :test**
Put one gem in a group

group :development, :test do ... end
Group several gems