Celery Python task queue

CONCEPTS

> The caller only publishes a message; a separate worker process runs the task. No worker, no work.

Your app task.delay()
↓ publish
Broker RabbitMQ or Redis
↓ consume
Worker runs the task
↓ store
Result backend optional, for .get()

WORKER

`celery -A proj worker -l INFO`
Start a worker

`-c` *<n>*
Number of pool processes

`-Q` *<q1>*`,`*<q2>*
Consume only these queues

`-n` *<name>*`@%h`
Set the node name

DEFINE AND CALL

`@app.task`
Declare a task

`@app.task(bind=True)`
Get self for retry and request

`add.delay(2, 3)`
Queue with plain arguments

`add.apply_async((2, 3), countdown=10)`
Queue with options

`apply_async(queue="`*<q>***`")`**
Send to a named queue

`add.s(2, 3)`
Signature: a task call as data

`res.get(timeout=`*<s>***`)`**
Block for the result

`res.ready() / res.state`
Check for completion

CANVAS

`chain(a.s(), b.s())`
Pipe each result into the next

`a.s() | b.s() | c.s()`
Chain with the pipe operator

`group(a.s(i) for i in r)`
Run many tasks in parallel

`chord(group)(callback.s())`
Run a callback after the group

> A chain passes each return value as the first argument of the next task; use .si() to ignore it.

RETRIES AND ERRORS

`self.retry(exc=e, countdown=`*<s>***`)`**
Retry the task later

`autoretry_for=(`*<Exc>***`,)`**
Retry automatically on these errors

`max_retries=`*<n>*
Give up after n retries

ROUTING AND CONFIG

`task_routes = {"`*<task>***`": {"queue": "`***<q>***`"}}`**
Route tasks to queues

`broker_url = "redis://localhost:6379/0"`
Set the broker

PERIODIC TASKS

`beat_schedule = {...}`
Declare the schedule

`crontab(hour=7, minute=30)`
Cron-style schedule

INSPECT AND CONTROL

`celery -A proj status`
Workers that answer

`celery -A proj inspect active`
Tasks running now