Checkov IaC security scanner

CONCEPTS

Checkov scans infrastructure-as-code (Terraform, Kubernetes, Dockerfiles, CloudFormation, CI configs) for misconfigurations without deploying anything.

IaC files tf, yaml, Dockerfile
↓ `checkov -d`
Framework runners auto-detected
↓ policies
Checks CKV_* IDs
↓ `-o`
Report pass / fail / skip

Every check has an ID like CKV_AWS_20; you use these IDs to select, skip and suppress checks.

By default all matching frameworks run; narrow with --framework to speed up large repos.

SETUP

`pip install checkov`
Install with pip

`checkov --version`
Show the version

`checkov --help`
List all options

`checkov --list`
List available checks

SCANNING

`checkov -d <dir>`
Scan a directory recursively

`checkov -f <file>`
Scan a single file

`checkov -f <a.tf> -f <b.tf>`
Scan several files

`checkov -f tfplan.json --repo-root-for-plan-enrichment <dir>`
Scan a Terraform plan

`checkov -d <dir> --skip-path <regex>`
Ignore paths matching a regex

SCANNING (cont.)

`checkov -d <dir> --download-external-modules true`
Fetch remote Terraform modules

FRAMEWORKS

`checkov -d <dir> --framework <name>`
Run only these frameworks

`checkov -d <dir> --skip-framework <name>`
Leave frameworks out

`checkov -d <dir> --framework secrets`
Hunt for hard-coded secrets

`checkov -d <dir> --framework kubernetes helm`
Scan manifests and charts

`checkov -d <dir> --framework dockerfile`
Lint Dockerfiles

`checkov -d <dir> --framework github_actions`
Scan GitHub workflows

Common names: terraform, terraform_plan, kubernetes, helm, kustomize, dockerfile, cloudformation, arm, bicep, github_actions, gitlab_ci, secrets.

CHOOSING CHECKS

`checkov -d <dir> -c <id>,<id>`
Run only these checks

`checkov -d <dir> --skip-check <id>,<id>`
Skip these checks

`checkov -d <dir> --external-checks-dir <dir>`
Load custom Python or YAML checks

OUTPUT

`checkov -d <dir> --compact`
Hide code snippets

`checkov -d <dir> --quiet`
Show only failed checks

`checkov -d <dir> -o <format>`
Pick an output format

OUTPUT (cont.)

`checkov -d <dir> -o json`
JSON report

`checkov -d <dir> -o sarif`
SARIF for code scanning

`checkov -d <dir> -o junitxml`
JUnit report for CI

`checkov -d <dir> -o cli -o json --output-file-path console,<file>`
Print and save in one run

`checkov -d <dir> --output-file-path <dir>`
Save reports in a folder

EXIT CODES AND CI

`checkov -d <dir> --soft-fail`
Always exit 0

`checkov -d <dir> --hard-fail-on <id|sev>`
Fail only on these checks

`checkov -d <dir> --soft-fail-on <id|sev>`
Pass when only these fail

BASELINES

`checkov -d <dir> --create-baseline`
Save current findings as a baseline

`checkov -d <dir> --baseline <file>`
Report only new failures

SUPPRESSING FINDINGS

Terraform: inside the resource

```
resource "aws_s3_bucket" "site" {
  #checkov:skip=CKV_AWS_20:public static site
}
```

Kubernetes: annotation

```
metadata:
  annotations:
    checkov.io/skip1: CKV_K8S_20=needs root for init
```

CONFIG FILE

`checkov --config-file <file>`
Use a YAML config file