chmod and chown

File permissions

CONCEPTS

Mode digits are sums per class: r=4, w=2, x=1. 640 means owner rw-, group r--, others ---.

On directories, r lists names, w creates or deletes entries, x lets you enter and access items by name.

chown normally needs root. chmod works only for the file owner or root.

OCTAL MODES

chmod 644 *<file>*
rw for owner, r for rest

chmod 755 *<file>*
rwx for owner, rx for rest

chmod 600 *<file>*
Private to owner

SYMBOLIC MODES

chmod +x *<file>*
Add execute (per umask)

chmod u+x *<file>*
Add execute for owner

chmod g+w *<file>*
Let group write

chmod o-rwx *<file>*
Remove all access for others

chmod u=rw,go=r *<file>*
Set classes exactly

RECURSIVE CHANGES

chmod -R *<mode> <dir>*
Recurse into a directory

chmod -R a+rX *<dir>*
Read all, x only on dirs

chmod -R u=rwX,go=rX *<dir>*
Sane tree permissions

find *<dir>* **-type d -exec chmod 755 {} +**
Dirs only

find *<dir>* **-type f -exec chmod 644 {} +**
Files only

SPECIAL BITS

chmod u+s *<file>*
Setuid: run as file owner

chmod g+s *<dir>*
Setgid dir: new files keep group

chmod +t *<dir>*
Sticky: only owners may delete

READING AND COPYING MODES

ls -l *<path>*
Long listing with mode

ls -ld *<dir>*
Mode of the dir itself

stat -c '%a %U:%G %n' *<file>*
Octal mode and owner

CHOWN

chown *<user> <file>*
Change owner

chown *<user>*:*<group> <file>*
Change owner and group

chown :*<group> <file>*
Change group only

chown -R *<user>*:*<group> <dir>*
Recursive ownership

sudo chown -R $USER: *<dir>*
Reclaim files made by root

UMASK

umask
Show current mask

umask 022
New files 644, dirs 755

umask removes bits from 666 for files and 777 for dirs. It only affects files created later by that shell and its children.

RECIPES

Web content tree

```
find /srv/www -type d -exec chmod 755 {}
+
find /srv/www -type f -exec chmod 644 {}
+
chown -R www-data:www-data /srv/www
```