Cilium CLI Kubernetes networking CLI

CONCEPTS

The cilium CLI talks to the cluster in your kubeconfig and manages the install; hubble is a separate binary for reading flows.

cilium CLI install and manage
↓ deploys
Agent + operator per node, eBPF
↓ flows to
Hubble Relay cluster-wide
↓ queried by
hubble CLI / UI observe flows

Every command takes --context to target another cluster in your kubeconfig.

INSTALL

cilium install
Install Cilium with detected defaults

cilium install --version *<ver>*
Install a specific release

cilium install --set *<key>*=*<value>*
Pass a Helm value

cilium install --dry-run
Show resources without applying

cilium install --dry-run-helm-values
Show non-default Helm values

cilium upgrade --version *<ver>*
Upgrade to a release

cilium upgrade --reuse-values --set *<key>*=*<value>*
Change one value on upgrade

cilium uninstall
Remove Cilium

STATUS AND CONFIG

cilium status
Show component health

STATUS AND CONFIG (cont.)

cilium status --wait
Block until Cilium is ready

cilium config view
Print the agent configuration

cilium sysdump
Collect a debug archive

CONNECTIVITY

cilium connectivity test
Run the end-to-end test suite

HUBBLE

cilium hubble enable
Deploy Hubble and Relay

cilium hubble port-forward
Forward Relay to localhost:4245

hubble status
Check Relay and flow counts

hubble observe
Stream recent flows

hubble observe -P
Auto port-forward Relay first

hubble observe --pod *<name>*
Flows for one pod

hubble observe --verdict DROPPED
Only dropped traffic

CLUSTER MESH

cilium install --set cluster.name=*<name>* **--set cluster.id=***<n>*
Give each cluster a unique name and ID

cilium clustermesh enable --context *<ctx>*
Deploy the mesh API server

cilium clustermesh status --wait
Wait for the mesh to be ready

cilium clustermesh connect --destination-context *<ctx>*
Connect two clusters