CMake Build system generator

CONCEPTS

CMake does not build anything itself: it generates files for a native tool (Make, Ninja, Visual Studio), which then compiles. Keep the build tree out of the source tree.

CMakeLists.txt project description
↓ configure
Build tree cache + generated files
↓ --build
Binaries via Make/Ninja
↓ ctest / --install
Tests, install results, prefix

Configure once, then build, test and install from the same tree

Cache variables (-D) persist in build/CMakeCache.txt, so later runs reuse them. Use --fresh or delete the build dir to reset.

CONFIGURE

cmake -S *<src>* **-B** *<build>*
Configure source into build dir

cmake -B build -G "*<generator>***"**
Choose generator (Ninja, Unix Makefiles)

cmake -B build -D*<VAR>***=***<value>*
Set a cache entry

cmake -B build -DCMAKE_BUILD_TYPE=*<type>*
Debug, Release, RelWithDebInfo

cmake -B build --fresh
Drop the cache and reconfigure

-DCMAKE_EXPORT_COMPILE_COMMANDS=ON
Write compile_commands.json

BUILD

cmake --build *<dir>*
Build everything

cmake --build *<dir>* **-j** *<N>*
Build with N parallel jobs

BUILD (cont.)

cmake --build *<dir>* **-t** *<target>*
Build one target

cmake --build *<dir>* **--config** *<cfg>*
Choose config (multi-config generators)

cmake --build *<dir>* **-v**
Show full compiler commands

INSTALL AND TEST

cmake --install *<dir>*
Install the project

cmake --install *<dir>* **--prefix** *<dir>*
Override the install prefix

ctest --test-dir *<dir>*
Run all tests

ctest --test-dir *<dir>* **--output-on-failure**
Show output of failing tests

INSPECT AND DEBUG

cmake -L -N *<dir>*
List cache variables, no reconfigure

CMAKELISTS.TXT

cmake_minimum_required(VERSION *<x.y>***)**
Declare the minimum CMake version

project(*<name>* **VERSION** *<x.y>* **LANGUAGES CXX)**
Name the project

add_executable(*<tgt>* *<sources>***)**
Define an executable target

add_library(*<tgt>* **STATIC|SHARED** *<sources>***)**
Define a library target

target_link_libraries(*<tgt>* **PRIVATE** *<lib>***)**
Link a dependency

find_package(*<Pkg>* **REQUIRED)**
Locate an installed package