gzip, xz and zstd Compress files

START HERE

`gzip` *`<file>`*
Compress, replacing the file

`zstd -d` *`<file.zst>`*
Decompress zstd

`gzip -d` *`<file.gz>`*
Decompress

`zcat` *`<file.gz>`*
Read without unpacking

`xz -k` *`<file>`*
Smaller, slower, keep original

`gzip -t` *`<file.gz>`*
Test integrity

`zstd` *`<file>`*
Fast and good, keeps original

`tar -caf` *`<out.tar.zst>`* *`<dir>`*
Compress a whole directory

gzip fast, universal → **zstd** fast, modern → **xz** smallest, slow

CONCEPTS

gzip and xz delete the input file by default; zstd keeps it. Add -k to gzip/xz, or --rm to zstd to delete.

These tools compress single streams, not folders. Use tar to bundle a directory first (tar -caf picks the compressor from the suffix).

Rule of thumb: gzip for compatibility, zstd for speed and everyday use, xz for archives that are written once and downloaded often.

Higher levels cost far more time than they save space. xz -7 to -9 also need much more memory to decompress.

Already-compressed data (jpg, mp4, zip, .gz) barely shrinks; compressing it again just wastes time.

GZIP

`gzip` *`<file>`*
Compress to <file>.gz, remove original

`gzip -k` *`<file>`*
Compress, keep the original

`gzip -d` *`<file.gz>`*
Decompress (same as gunzip)

`gzip -c` *`<file>`* `>` *`<out.gz>`*
Write to stdout, keep original

`gzip -9` *`<file>`*
Best compression (slowest)
Levels are -1 (fast) to -9 (best); the default is -6.

`gzip -1` *`<file>`*
Fastest compression

`gzip -r` *`<dir>`*
Compress every file below a dir
Each file becomes its own .gz; it does not make an archive.

`gzip -n` *`<file>`*
Do not store name and timestamp
Makes output reproducible for identical input.

XZ

`xz` *`<file>`*
Compress to <file>.xz, remove original

`xz -k` *`<file>`*
Compress, keep the original

XZ (cont.)

`xz -d` *`<file.xz>`*
Decompress (same as unxz)

`xz -c` *`<file>`* `>` *`<out.xz>`*
Write to stdout, keep original

`xz -9` *`<file>`*
Strong compression, high memory
Presets -0 to -9; default is -6.

`xz -9e` *`<file>`*
Extreme: a bit smaller, much slower

`xz -T0` *`<file>`*
Use all CPU cores
Threaded output is split into blocks, so it is slightly larger. In xz 5.8 the default is already -T0.

`xz -T`*`<n>`* *`<file>`*
Use at most n threads

ZSTD

`zstd` *`<file>`*
Compress to <file>.zst, keep original

`zstd -d` *`<file.zst>`*
Decompress (same as unzstd)

`zstd -o` *`<out>`* *`<file>`*
Choose the output name

`zstd -c` *`<file>`* `>` *`<out.zst>`*
Write to stdout

`zstd --rm` *`<file>`*
Delete input after success

`zstd -19` *`<file>`*
High compression, slower
Levels 1-19, default 3. --ultra unlocks 20-22 and needs lots of memory.

`zstd --fast=`*`<n>`* *`<file>`*
Faster than level 1, larger output

`zstd -T0` *`<file>`*
Use all CPU cores
Default is a single thread.

`zstd --long=27` *`<file>`*
Long-distance matching, 128 MB window
Helps with big files with far-apart repeats. The decompressor needs --long=27 too (or --memory) for windows over 128 MB.

`zstd --ultra -22` *`<file>`*
Maximum compression

`zstd --adapt` *`<file>`*
Tune level to I/O speed
Good when piping to a slow network.

`zstd -b`*`<n>`* *`<file>`*
Benchmark level n on a file

ZSTD (cont.)

`zstd -f` *`<file>`*
Overwrite existing output

READ AND INSPECT

`zcat` *`<file.gz>`*
Print decompressed content

`xzcat` *`<file.xz>`*
Print decompressed content

`zstdcat` *`<file.zst>`*
Print decompressed content

`zcat` *`<file.gz>`* `| less`
Page through a compressed file

`zgrep` *`<pat>`* *`<file.gz>`*
Search without unpacking
xzgrep and zstdgrep work the same way.

`zless` *`<file.gz>`*
Browse a compressed file

`gzip -l` *`<file.gz>`*
Show sizes and ratio
The uncompressed size is wrong for files over 4 GiB.

`xz -l` *`<file.xz>`*
Show sizes, check and blocks

`zstd -l` *`<file.zst>`*
Show frames, sizes, ratio

TEST AND CHECK

`gzip -t` *`<file.gz>`*
Test integrity, silent if ok

`xz -t` *`<file.xz>`*
Test integrity

`zstd -t` *`<file.zst>`*
Test integrity

`gzip -tv` *`<file.gz>`*
Test and print result

PIPES AND ARCHIVES

`<cmd>` `|` **`gzip >`** *`<out.gz>`*
Compress a stream

`gzip -dc` *`<file.gz>`* `|` *`<cmd>`*
Decompress into a pipe

`<cmd>` `|` **`zstd -T0 | ssh`** *`<host>`* **`'cat >`** *`<out.zst>`***`'`**
Compress before sending

`tar -caf` *`<out.tar.zst>`* *`<dir>`*
Archive, compressor from suffix

`tar -I 'zstd -T0 -19' -cf` *`<out.tar.zst>`* *`<dir>`*
Archive with custom options

PIPES AND ARCHIVES (cont.)

`tar -xf` *`<out.tar.zst>`*
Extract any tar compression

`tar -I pigz -cf` *`<out.tar.gz>`* *`<dir>`*
Parallel gzip if pigz is installed

ZIP AND UNZIP

`zip -r` *`<out.zip>`* *`<dir>`*
Zip a directory

`zip` *`<out.zip>`* *`<file>`*`...`
Zip some files

`unzip` *`<file.zip>`*
Extract here

`unzip` *`<file.zip>`* `-d` *`<dir>`*
Extract into a directory

`unzip -l` *`<file.zip>`*
List contents

`unzip -t` *`<file.zip>`*
Test integrity

`unzip` *`<file.zip>`* *`<member>`*
Extract one member

WHICH FORMAT

Compared

Tool	Speed	Size	Use for
`gzip`	fast	medium	compatibility, logs
`zstd`	very fast	good	everyday, backups
`xz`	slow	smallest	release tarballs
`zip`	fast	medium	sharing with Windows

RECIPES

Max-compress a big file using all cores

```
zstd -19 -T0 --long=27 big.img
# decompress: zstd -d --long=27
big.img.zst
```

Compress a database dump on the fly

```
pg_dump mydb | zstd -T0 >
mydb.sql.zst
zstdcat mydb.sql.zst | psql mydb
```

Compress every log older than a day

```
find /var/log/app -name '*.log'
-mtime +1 \
  -exec gzip {} +
```

Compare formats on your data

```
for c in 'gzip -9' 'zstd -19'
'xz -9'; do
  printf '%s: ' "$c"; $c -c data
| wc -c
done
```