File commands (ls, cp, mv, ln)

Everyday file handling

CONCEPTS

No trash can: rm and overwriting cp/mv are permanent. Add -i or -n while learning, and expand globs with echo first.

A hard link is another name for the same inode (same filesystem, files only). A symlink is a small file holding a path and can dangle.

LISTING (LS)

ls
List the current directory

ls -l
Long format: mode, owner, size, date

ls -a
Include hidden dotfiles

ls -lh
Human-readable sizes

ls -lt
Newest first

COPYING (CP)

cp *<src> <dst>*
Copy a file

cp -r *<dir> <dst>*
Copy a directory recursively

cp -a *<src> <dst>*
Archive: recurse, keep links, mode, times

cp -i *<src> <dst>*
Ask before overwriting

MOVING (MV)

mv *<src> <dst>*
Move or rename

mv *<a> <b> <dir>*
Move several items into a directory

mv -i *<src> <dst>*
Ask before overwriting

REMOVING (RM, RMDIR)

rm *<file>*
Delete a file

rm -i *<file>*
Confirm each deletion

rm -r *<dir>*
Delete a directory tree

rm -rf *<dir>*
Recursive, no prompts, ignore missing

rm -I *<files>*
One prompt for 4+ files or recursion

rmdir *<dir>*
Remove an empty directory only

LINKS (LN, READLINK)

ln -s *<target> <link>*
Create a symbolic link

ln -sf *<target> <link>*
Replace an existing link

ls -l *<link>*
Show where a link points

DIRECTORIES AND FILES

mkdir *<dir>*
Create a directory

mkdir -p *<a/b/c>*
Create parents, no error if present

touch *<file>*
Create empty file or update its time

INSPECTING PATHS

stat *<file>*
Size, inode, mode, owner, times

TEMPORARY FILES (MKTEMP)

mktemp
Create a unique temp file, print its path

mktemp -d
Create a unique temp directory