Cosign Sign and verify artifacts

CONCEPTS

Sign by digest (image@sha256:...), not by tag: a tag can move to a different image after you sign.

OIDC login Google, GitHub, ...
↓ identity token
Fulcio short-lived cert
↓ sign with ephemeral key
Signature stored in registry
↓ log entry
Rekor transparency log
Keyless signing

Keyless verify needs both an expected identity and an expected OIDC issuer; without them anyone with any Sigstore identity would pass.

Signatures and attestations are stored as extra artifacts next to the image in the same registry, so signing needs push access.

KEYS

cosign generate-key-pair
Create cosign.key and cosign.pub

cosign generate-key-pair --output-key-prefix *<name>*
Choose the key file names

--key awskms:// / gcpkms:// / azurekms:// / hashivault://
Key in a KMS (URI schemes)

SIGN

cosign sign --key cosign.key *<image>*@*<digest>*
Sign with a local key

cosign sign *<image>*@*<digest>*
Keyless sign (OIDC login)

cosign sign --yes *<image>*@*<digest>*
Skip confirmation prompts (CI)

VERIFY

cosign verify --key cosign.pub *<image>*
Verify with a public key

VERIFY (cont.)

cosign verify --certificate-identity *<id>* **--certificate-oidc-issuer** *<url>* *<image>*
Verify a keyless signature

cosign verify --key cosign.pub *<image>* **| jq**
Read the verified payload

ATTESTATIONS

cosign attest --key cosign.key --predicate *<file>* *<image>*@*<digest>*
Attach a signed predicate

cosign attest --type *<type>* **--predicate** *<file>* *<image>*@*<digest>*
Set the predicate type

cosign verify-attestation --key cosign.pub *<image>*
Verify attestations

cosign verify-attestation --type *<type>* **--policy** *<file>* **--key cosign.pub** *<image>*
Check predicate against a policy

cosign verify-attestation ... *<image>* **| jq -r .payload | base64 -d**
Decode the statement

BLOBS

cosign sign-blob --bundle *<bundle>* *<file>*
Keyless sign a file into a bundle

cosign verify-blob --bundle *<bundle>* **--certificate-identity** *<id>* **--certificate-oidc-issuer** *<url>* *<file>*
Verify a keyless file signature

cosign sign-blob --key cosign.key *<file>*
Sign a file with a key

cosign verify-blob --key cosign.pub --bundle *<bundle>* *<file>*
Verify a file with a public key

INSPECT AND MANAGE

cosign tree *<image>*
Show signatures, SBOMs, attestations

INSPECT AND MANAGE (cont.)

cosign login *<registry>*
Log in to a registry

cosign version
Print the cosign version

ENVIRONMENT

COSIGN_PASSWORD=*<pw>*
Key password without a prompt

SIGSTORE_ID_TOKEN=*<token>*
Supply an OIDC token, skip login

cosign env --show-descriptions
List all variables cosign reads

In CI (GitHub Actions) keyless signing picks up the workflow's OIDC token automatically; the job needs id-token: write.

RECIPES

Key-based sign and verify

```
cosign generate-key-pair
cosign sign --key cosign.key
ghcr.io/me/app@sha256:<digest>
cosign verify --key cosign.pub
ghcr.io/me/app@sha256:<digest>
```

Keyless in CI, verify by identity

```
cosign sign --yes ghcr.io/me/
app@sha256:<digest>
cosign verify ghcr.io/me/
app@sha256:<digest> \
  --certificate-identity-regexp
'https://github.com/me/app/.*' \
  --certificate-oidc-issuer
https://token.actions.
githubusercontent.com
```

Sign a release file

```
cosign sign-blob --yes --bundle
app.tgz.sigstore.json app.tgz
cosign verify-blob --bundle
app.tgz.sigstore.json \
  --certificate-identity <id> --
certificate-oidc-issuer <url>
app.tgz
```

Attach and check an SBOM attestation

```
cosign attest --key cosign.key --
type spdxjson --predicate
sbom.spdx.json <image>@<digest>
cosign verify-attestation --key
cosign.pub --type spdxjson
<image>@<digest>
```