Cppcheck C/C++ static analyser

START HERE

cppcheck *<path>*
Check files or a folder

cppcheck --enable=all *<path>*
Turn on more checks

cppcheck -I *<dir>* *<path>*
Add an include path

cppcheck --project= compile_commands.json
Check what you build

cppcheck -j 4 *<path>*
Use 4 threads

cppcheck --std=c++17 *<path>*
Pick the language standard

cppcheck --suppress=*<id>* *<path>*
Silence one message

cppcheck --error-exitcode=1 *<path>*
Fail the build on findings

Sources files or project → preprocess → **Configurations** #ifdef variants → analyse → **Checks** --enable ids → report → **Findings** text / XML

CONCEPTS

By default only errors are shown. Add --enable=style (or all) to see warnings, style and performance findings.

Cppcheck tries each #ifdef configuration itself, so missing -I paths and -D flags give fewer findings, not errors. Use --check-config to see what it could not resolve.

RUNNING

cppcheck *<file>*
Check one file

cppcheck *<dir>*
Check all sources in a folder, recursively

cppcheck -j *<n>* *<dir>*
Check with n threads

cppcheck -q *<dir>*
Quiet: print only findings

cppcheck -i *<path>* *<dir>*
Skip a file or folder
Example: -isrc/third_party. Matches by path prefix or pattern.

cppcheck *<dir>* **--file-filter=***<pattern>*
Check only matching files

cppcheck --language=c++ *<file>*
Force C or C++ for all files

RUNNING (cont.)

cppcheck --showtime=summary *<dir>*
Show where the time goes

CHECKS AND LEVELS

cppcheck --enable=warning *<dir>*
Add warnings

cppcheck --enable=style *<dir>*
Add style findings

cppcheck --enable=performance,portability *<dir>*
Add several groups (comma list)

cppcheck --enable=all *<dir>*
Enable every group
all includes unusedFunction, which gives false positives unless you pass the whole program.

cppcheck --enable=unusedFunction *<dir>*
Find unused functions

cppcheck --enable=missingInclude *<dir>*
Report unresolved includes

cppcheck --check-level=exhaustive *<dir>*
Deeper, slower analysis

CHECKS AND LEVELS (cont.)

cppcheck --inconclusive *<dir>*
Also report uncertain findings

cppcheck --check-config *<dir>*
Show missing includes and config problems

CONFIGURATION

cppcheck -I *<dir>* *<path>*
Add an include directory

cppcheck -D*<name>* *<path>*
Define a macro, check only that config

cppcheck -U*<name>* *<path>*
Treat a macro as undefined

cppcheck --max-configs=*<n>* *<path>*
Limit #ifdef configurations tried

cppcheck --force *<path>*
Check every configuration (can be slow)

cppcheck --std=c++20 *<path>*
Set the C++ standard
C++: c++03 to c++26. C: c89, c99, c11, c17, c23.

cppcheck --std=c11 *<file>*
Set the C standard

CONFIGURATION (cont.)

cppcheck --platform=*<name>* *<path>*
Set target types and sizes
Builtin names include unix32, unix64, win32A, win32W, win64. Custom platforms use an XML file.

cppcheck --library=*<name>* *<path>*
Load a library config (posix, qt, ...)

PROJECTS AND INCREMENTAL RUNS

cppcheck --project= compile_commands.json
Use a compilation database

cppcheck --project=*<file>***.sln**
Import a Visual Studio solution

cppcheck --project=*<file>***.cppcheck**
Use a GUI project file

cppcheck --project= compile_commands.json -i*<dir>*
Exclude a folder from a project

cppcheck --cppcheck-build-dir=*<dir>* *<path>*
Cache results, enable whole-program checks
Reuse the same folder between runs for incremental analysis. Needed for cross-file checks with -j.

OUTPUT

cppcheck --template=gcc *<path>*
GCC-style lines for editors

cppcheck --template='{file}:{line}: {message}' *<path>*
Custom line format
Other fields: {callstack}, {code}, {inconclusive:text}, {remark}. Use \n and \t for breaks.

cppcheck --xml *<path>* **2>** *<out.xml>*
XML report (written to stderr)

cppcheck-htmlreport --file=*<out.xml>* **--report-dir=***<dir>* **--source-dir=.**
Turn XML into an HTML report
Needs Python and pygments.

cppcheck -rp *<path>*
Print paths relative to a base

cppcheck --error-exitcode=*<n>*
Exit with n when findings exist

SUPPRESSIONS

cppcheck --suppress=*<id>* *<path>*
Suppress an id everywhere

cppcheck --suppress=*<id>***:***<file>* *<path>*
Suppress an id in one file
*Wildcards *, ** and ? work in the file part.*

SUPPRESSIONS (cont.)

cppcheck --suppress=*<id>***:***<file>***:***<line>* *<path>*
Suppress at one line

cppcheck --suppressions-list=*<file>* *<path>*
Read suppressions from a text file
One per line, same format as --suppress. # and // start comments.

cppcheck --inline-suppr *<path>*
Honour cppcheck-suppress comments

// cppcheck-suppress *<id>*
Suppress on the next or same line

// cppcheck-suppress [*<id1>***, ***<id2>***]**
Suppress several ids at once

// cppcheck-suppress-begin *<id>* **... -end** *<id>*
Suppress a block

// cppcheck-suppress-file *<id>*
Suppress for the whole file

ADDONS

cppcheck --addon=*<name>***.py** *<path>*
Run a Python addon

cppcheck --addon=*<file>***.json** *<path>*
Run an addon with settings
JSON keys: script, args, ctu.