cron Scheduled jobs

CONCEPTS

Cron wakes every minute and runs jobs whose five time fields match. Jobs run with a minimal environment and no terminal, so use absolute paths and set PATH yourself.

If both day-of-month and day-of-week are restricted (not *), the job runs when either matches, not both. 30 4 1,15 * 5 runs on the 1st, the 15th and every Friday.

MANAGING CRONTABS

crontab -e
Edit your crontab in $EDITOR

crontab -l
Show your installed crontab

crontab -r
Remove your crontab, no confirmation

crontab -i -r
Ask before removing

crontab *<file>*
Replace your crontab with a file

SCHEDULE SYNTAX

*** * * * *** *<cmd>*
Every minute

***/15 * * * *** *<cmd>*
Every 15 minutes

0 * * * * *<cmd>*
Top of every hour

30 4 * * * *<cmd>*
Every day at 04:30

0 9 * * 1-5 *<cmd>*
Weekdays at 09:00

0 0 1 * * *<cmd>*
First of the month at midnight

0 8,12,18 * * * *<cmd>*
List: 08:00, 12:00, 18:00

SPECIAL STRINGS

@reboot
Once when the cron daemon starts

@hourly
Same as 0 * * * *

@daily / @midnight
Same as 0 0 * * *

@weekly
Same as 0 0 * * 0

ENVIRONMENT AND OUTPUT

PATH=/usr/local/bin:/usr/bin:/bin
Set PATH at the top (no $PATH)

SHELL=/bin/bash
Choose the shell for commands

MAILTO=*<addr>*
Mail job output to this address

MAILTO=""
Never mail output

<cmd> **>>** *<log>* **2>&1**
Append stdout and stderr to a log

<cmd> **> /dev/null 2>&1**
Discard all output

date +\%F
Escape % with a backslash

DEBUGGING

grep CRON /var/log/syslog
See cron run lines (needs rsyslog)

journalctl -u cron
Cron log on systemd (cron.service on Debian)

RECIPES

Typical crontab header

```
SHELL=/bin/bash
PATH=/usr/local/bin:/usr/bin:/bin
MAILTO=you@example.com
# m  h  dom mon dow  command
15 3 * * *  /home/me/bin/backup.sh >> /
home/me/backup.log 2>&1
```