cryptsetup Disk encryption

Block device /dev/sdb1 → open → **Mapping** /dev/mapper/<name> → mount → **Filesystem** readable data

CONCEPTS

luksFormat destroys all data on the device. Double-check the device name with lsblk first.

Without the LUKS header the data is gone for good. Keep a header backup somewhere safe, off the disk itself.

New volumes default to LUKS2. Use --type luks1 only for old tools, such as some bootloaders.

CREATE

`cryptsetup luksFormat <device>`
Encrypt a device with LUKS

`cryptsetup luksFormat --type luks1 <device>`
Use the older LUKS1 format

`cryptsetup luksFormat --cipher <cipher> --key-size <bits> <device>`
Choose cipher and key size

`cryptsetup benchmark`
Measure cipher speed

`cryptsetup isLuks <device>`
Exit status 0 if it is LUKS

OPEN AND CLOSE

`cryptsetup open <device> <name>`
Unlock and map a device

`cryptsetup close <name>`
Remove the mapping and wipe the key

`cryptsetup status <name>`
Show an active mapping

`cryptsetup open --key-file <file> <device> <name>`
Unlock with a key file

`cryptsetup open --readonly <device> <name>`
Unlock read-only

`cryptsetup open --allow-discards <device> <name>`
Pass TRIM through to the disk

`cryptsetup open --header <file> <device> <name>`
Use a detached header

`cryptsetup open --test-passphrase <device>`
Check a passphrase only

`cryptsetup luksSuspend <name>`
Freeze I/O and wipe the key

`cryptsetup luksResume <name>`
Unlock a suspended volume

KEY SLOTS

`cryptsetup luksAddKey <device>`
Add another passphrase

`cryptsetup luksAddKey <device> <keyfile>`
Add a key file

`cryptsetup luksChangeKey <device>`
Change a passphrase

`cryptsetup luksRemoveKey <device>`
Remove the passphrase you type

`cryptsetup luksKillSlot <device> <slot>`
Remove a slot by number

`dd if=/dev/urandom of=<keyfile> bs=512 count=8`
Make a random key file

INSPECT AND HEADER

`cryptsetup luksDump <device>`
Show header, slots and digests

`cryptsetup luksUUID <device>`
Print the UUID

INSPECT AND HEADER (cont.)

`cryptsetup luksHeaderBackup <device> --header-backup-file <file>`
Save the header to a file

`cryptsetup luksHeaderRestore <device> --header-backup-file <file>`
Restore a saved header

`cryptsetup erase <device>`
Remove all key slots

`blkid <device>`
Show type crypto_LUKS and UUID

RESIZE

`cryptsetup resize <name>`
Grow mapping to fill the device

`resize2fs /dev/mapper/<name>`
Grow an ext4 filesystem

BOOT AND FSTAB

`echo "<name> UUID=<uuid> none luks" >> /etc/crypttab`
Unlock at boot

BOOT AND FSTAB (cont.)

`echo "/dev/mapper/<name> <dir> ext4 defaults 0 2" >> /etc/fstab`
Mount after unlock

RECIPES

Encrypt a new USB stick

```
# find the device first
lsblk
cryptsetup luksFormat /dev/sdX1
cryptsetup open /dev/sdX1 usb
mkfs.ext4 /dev/mapper/usb
mount /dev/mapper/usb /mnt
```

Unlock, use, lock

```
cryptsetup open /dev/sdX1 usb
mount /dev/mapper/usb /mnt
# work
umount /mnt
cryptsetup close usb
```

Back up the header

```
cryptsetup luksHeaderBackup /dev/sdX1 \
  --header-backup-file usb-header.img
cryptsetup luksDump /dev/sdX1
```

Rotate a passphrase

```
cryptsetup luksAddKey /dev/sdX1
cryptsetup luksRemoveKey /dev/sdX1
# type the old passphrase to remove it
```