curl Transfer data by URL

URL scheme, host, path → connect → **Request** method, headers, body → send → **Response** status, headers, body → output → **Output** stdout, -o, -O

CONCEPTS

curl prints the response body to stdout and progress to stderr, so it composes with pipes. It does not fail on HTTP 404/500 unless you add -f.

Quote URLs containing & or ? so the shell does not split them.

REQUESTS

curl *<url>*
GET a URL

curl -X *<method>* *<url>*
Set the request method

curl -d *<data>* *<url>*
POST form-encoded data

curl -d @*<file>* *<url>*
POST data from a file

curl --json '*<json>***'** *<url>*
POST JSON with proper headers

curl -F *<name>*=*<value>* *<url>*
Multipart form field

curl -F *<name>*=@*<file>* *<url>*
Upload a file as form field

REQUESTS (cont.)

curl -G -d *<k=v>* *<url>*
Send data as query string

curl --url-query *<k=v>* *<url>*
Add an encoded query param

curl --data-urlencode *<k=v>* *<url>*
URL-encode a POST value

curl -T *<file>* *<url>*
Upload with PUT

curl -I *<url>*
HEAD request, headers only

curl --data-binary @*<file>* *<url>*
POST file exactly as is

curl -X PATCH -d *<data>* *<url>*
Send a PATCH

HEADERS & AUTH

curl -H "*<name>***:** *<value>***"** *<url>*
Add a custom header

curl -u *<user>*:*<pass>* *<url>*
Basic authentication

curl -H "Authorization: Bearer *<token>***"** *<url>*
Send a bearer token

HEADERS & AUTH (cont.)

curl --oauth2-bearer *<token>* *<url>*
Bearer token shortcut

curl -A "*<agent>***"** *<url>*
Set the User-Agent

curl -b "*<name>*=*<value>***"** *<url>*
Send a cookie

curl -b *<jar>* **-c** *<jar>* *<url>*
Read and write a cookie file

OUTPUT & DOWNLOAD

curl -o *<file>* *<url>*
Save body to a file

curl -O *<url>*
Save under the remote name

curl -L *<url>*
Follow redirects

curl -i *<url>*
Include response headers

curl -s *<url>*
Silent: no progress meter

curl -sS *<url>*
Silent, but show errors

curl -f *<url>*
Fail on HTTP errors (22)

OUTPUT & DOWNLOAD (cont.)

curl --fail-with-body *<url>*
Fail on errors, keep body

curl -C - -O *<url>*
Resume a partial download

curl -D *<file>* *<url>*
Dump headers to a file

curl -w "*<format>***"** *<url>*
Print info after transfer

curl --compressed *<url>*
Ask for and decode gzip/br

NETWORK & TLS

curl -k *<url>*
Skip certificate checks

curl --cacert *<file>* *<url>*
Trust a specific CA

curl --cert *<file>* **--key** *<key>* *<url>*
Client certificate

curl -x *<proxy>* *<url>*
Use a proxy

curl --resolve *<host>*:*<port>*:*<ip>* *<url>*
Pin a hostname to an IP

curl --connect-timeout *<s>* *<url>*
Limit connect time

NETWORK & TLS (cont.)

curl -m *<s>* *<url>*
Limit total time

curl --retry *<n>* *<url>*
Retry transient failures

DEBUGGING

curl -v *<url>*
Verbose request and response

curl --trace-ascii *<file>* *<url>*
Full trace, readable

curl -w "%{time_total}\n" -o /dev/null -s *<url>*
Time a request

curl -sI *<url>*
Check headers quietly

curl --help all
List every option

curl "*<url>***[1-5].txt"**
URL globbing ranges

RECIPES

POST JSON and check status

```
curl -sS --fail-with-body \
  --json '{"name":"x"}' \
  -H "Authorization: Bearer $TOKEN" \
  https://api.example.com/items
```