Cypher Shell Neo4j graph CLI

CONCEPTS

Statements typed in the shell must end with a semicolon; lines starting with : are shell commands and need none.

cypher-shell your terminal
↓ Bolt
Neo4j server port 7687
↓ routes to
Database neo4j / system
↓ holds
Graph nodes + relationships

Patterns are drawn in ASCII art: (node)-[:REL]→(node). Labels start with a colon, properties go in braces.

CONNECT

`cypher-shell -u <user> -p <password>`
Connect to localhost

`cypher-shell -a <uri>`
Connect to another server

`cypher-shell -d <database>`
Start in a given database

SHELL COMMANDS

`:help`
List shell commands

`:exit`
Quit the shell

`:use <database>`
Set the active database

`:begin`
Open an explicit transaction

`:commit`
Commit the open transaction

SCRIPT & OUTPUT

`cypher-shell "<cypher>"`
Run one statement and exit

SCRIPT & OUTPUT (cont.)

`cypher-shell -f <file>`
Run a Cypher file and exit

`cypher-shell --format plain`
Minimal output for scripts

READ

`MATCH (n) RETURN n LIMIT <k>`
Sample some nodes

`MATCH (n:<Label>) RETURN n`
Nodes with a label

`MATCH (n:<Label> {<prop>: <value>}) RETURN n`
Match by property

`MATCH (a)-[r:<TYPE>]→(b) RETURN a, r, b`
Follow a relationship type

`WHERE n.<prop> > <value>`
Filter matches

`ORDER BY n.<prop> DESC`
Sort the rows

WRITE

`CREATE (:<Label> {<prop>: <value>})`
Create a node

`MERGE (n:<Label> {<prop>: <value>})`
Create only if missing

`SET n.<prop> = <value>`
Set a property

`DETACH DELETE n`
Delete a node and its relationships

PIPELINES

`WITH n, count(*) AS c`
Pass results to the next part

SCHEMA & ADMIN

`SHOW DATABASES`
List databases