Dagger Programmable CI pipelines

CONCEPTS

Functions run in containers on the Dagger engine, so a pipeline behaves the same on your laptop and in CI.

Your code module + SDK
↓ `dagger call`
CLI GraphQL API
↓ `session`
Engine BuildKit-based
↓ `runs`
Containers cached steps

Chain functions on the command line: each returned object exposes its own functions, such as container, directory and file.

MODULES

`dagger init --sdk=`*`<go|python|typescript>`*
Create a module in this directory

`dagger develop`
Regenerate SDK code and bindings

`dagger install` *`<module>`*
Add a module as dependency

`dagger update` *`<module>`*
Update a dependency

CALL FUNCTIONS

`dagger functions`
List the module's functions

`dagger functions` *`<fn>`*
List a function's sub-functions

`dagger call` *`<fn>`*
Run a function

`dagger call` *`<fn>`* **`--help`**
Show a function's arguments

`dagger call` *`<fn>`* **`--`***`<arg>`* *`<value>`*
Pass an argument

`dagger call` *`<fn>`* *`<next-fn>`*
Chain functions

CALL FUNCTIONS (cont.)

`dagger call` *`<fn>`* **`--source=.`**
Pass a local directory

`dagger call` *`<fn>`* **`stdout`**
Print a container's output

`dagger call` *`<fn>`* **`-o`** *`<path>`*
Save the result to a file or directory

`dagger call` *`<fn>`* **`terminal`**
Open a shell in the result container

`dagger call -m` *`<ref>`* *`<fn>`*
Call a module by path or git ref

SHELL AND API

`dagger`
Open the interactive Dagger shell

`dagger -c "`*`<script>`***`"`**
Run a Dagger shell script

`dagger core container from` *`<image>`*
Call the core API directly

`dagger run` *`<command>`*
Run any program inside a Dagger session

Shell, call or run?

Command	Use for
`dagger call`	functions in a module
`dagger (shell)`	exploring, ad-hoc pipelines
`dagger run`	your own SDK script

SECRETS

`dagger call` *`<fn>`* **`--token=env://`***`<VAR>`*
Secret from an env variable

`dagger call` *`<fn>`* **`--token=file://`***`<path>`*
Secret from a file

OUTPUT AND DEBUG

`dagger call -i` *`<fn>`*
Shell into a failing exec

`dagger call --progress=plain` *`<fn>`*
Plain log output for CI