diff and patch

Compare and patch files

CONCEPTS

diff makes the patch, patch applies it. Always preview with --dry-run first.

Old + new files two versions
↓ `diff -u`
Patch file + and - lines
↓ `patch -p1`
Patched tree new version

diff exit status

Code	Meaning
`0`	no differences
`1`	files differ
`2`	trouble (missing file, bad option)

In a patch, a/ and b/ prefixes are path components: -p1 strips one, -p0 none.

COMPARE FILES

`diff <a> <b>`
Show differences (normal format)

`diff -u <a> <b>`
Unified diff, the patch format

`diff -q <a> <b>`
Only say whether files differ

`diff --color=auto -u <a> <b>`
Colorize added and removed lines

`diff -y <a> <b>`
Two columns side by side

`diff -U <n> <a> <b>`
Unified diff with n context lines

`diff <(<cmd1>) <(<cmd2>)`
Compare the output of two commands

COMPARE DIRECTORIES

`diff -rq <dirA> <dirB>`
List files that differ or exist on one side

`diff -r <dirA> <dirB>`
Show all differences recursively

`diff -ru <dirA> <dirB>`
Recursive unified diff

`diff -rN <dirA> <dirB>`
Show added and removed files as full diffs

`diff -rq -x '<glob>' <dirA> <dirB>`
Skip files matching a glob

CREATE PATCHES

`diff -u <old> <new> > <name>.patch`
Patch for a single file

`diff -ruN <old-dir> <new-dir> > <name>.patch`
Patch for a directory tree

`cp -r <dir> <dir>.orig`
Keep a pristine copy before editing

`diff -ruN <dir>.orig <dir> > <name>.patch`
Diff the edited tree against the copy

Put the old tree first and the new one second, or the patch is reversed.

APPLY PATCHES

`patch -p1 < <name>.patch`
Apply a tree patch from its top directory

`patch <file> < <name>.patch`
Apply a patch to one named file

`patch -p1 --dry-run < <name>.patch`
Show what would happen, change nothing

`patch -R -p1 < <name>.patch`
Reverse an applied patch

`patch -p1 -d <dir> < <name>.patch`
Apply inside another directory

-p levels for a/src/main.c

Option	File patched
`-p0`	a/src/main.c
`-p1`	src/main.c
`-p2`	main.c

TROUBLESHOOTING

`find . -name '*.rej'`
Find hunks that did not apply

`cat <file>.rej`
Read a rejected hunk, then apply by hand

patch applies hunks that match and rejects the rest, so a failed run can leave a half-patched tree. Use --dry-run, or a clean checkout.

Wrong -p value gives "can't find file to patch". Compare the paths in the patch header with your current directory.