dig DNS lookups

CONCEPTS

dig talks to the DNS server directly and ignores /etc/hosts, so it can differ from what your applications resolve.

Your machine dig
↓ query
Resolver @server or resolv.conf
↓ +trace skips it
Root / TLD delegations
↓ refers to
Authoritative the final answer

Options starting with + change a query; options starting with - change dig itself. Order is free: name, type and @server may come anywhere.

BASIC QUERIES

dig *<name>*
Query A records

dig *<name>* *<type>*
Query a record type

dig -t *<type>* *<name>*
Same, with the type as a flag

dig *<name>* **AAAA**
IPv6 address

dig *<name>* **MX**
Mail servers

dig *<name>* **NS**
Name servers of a zone

dig *<name>* **TXT**
Text records (SPF, verification)

dig *<name>* **CNAME**
Alias target

dig *<name>* **SOA**
Zone start of authority and serial

CHOOSE THE SERVER

dig @*<server>* *<name>*
Ask this resolver or server

dig @1.1.1.1 *<name>*
Use a public resolver

dig @*<ns>* *<name>* **+norecurse**
Ask without recursion

dig +tcp *<name>*
Query over TCP

OUTPUT CONTROL

dig +short *<name>*
Print only the answer data

dig +noall +answer *<name>*
Answer section only, with TTLs

dig +noall +answer +ttlunits *<name>*
TTLs as 1h30m style

dig +multiline *<name>* **SOA**
Expand records over lines

dig +short -x *<ip>*
Reverse lookup, name only

REVERSE AND TRACING

dig -x *<ip>*
Reverse (PTR) lookup

dig +trace *<name>*
Walk from the root servers down

dig +nssearch *<zone>*
Ask every authoritative server for the SOA

dig NS *<zone>* **+short**
List the zone's name servers

BATCH AND CONFIG

dig -f *<file>*
Run lookups listed in a file

READING THE OUTPUT

Header flags

Item	Meaning
`status: NOERROR`	Query succeeded (answer may be empty)
`status: NXDOMAIN`	Name does not exist
`status: SERVFAIL`	Server could not answer
`status: REFUSED`	Server will not answer you
`flags: qr`	This is a response
`flags: aa`	Authoritative answer
`flags: rd ra`	Recursion asked / available
`flags: ad`	DNSSEC validated
`flags: tc`	Truncated, retry over TCP

NOERROR with an empty answer means the name exists but has no record of that type. NXDOMAIN means the name does not exist at all.