Dockerfile Image build recipe

START HERE

`FROM <image>:<tag>`
Pick a base image

`USER <user>`
Drop root

`WORKDIR /app`
Set the working directory

`CMD ["exe", "arg"]`
Default start command

`COPY <src> <dest>`
Add files from the context

`RUN <command>`
Run a command at build time

`ENV <key>=<value>`
Set an environment variable

`EXPOSE <port>`
Document a listening port

Base image FROM → **Layers** one per step (RUN / COPY) → **Final stage** what ships (cache) → **Container** running process (CMD)

CONCEPTS

Each instruction adds a layer, and a changed layer invalidates every layer after it. Put rarely changing steps first.

RUN, COPY and ADD happen at build time. CMD and ENTRYPOINT only describe what runs when a container starts.

BASE AND STAGES

`FROM <image>:<tag>`
Start from a base image
Without a tag you get latest. Pin a tag or an @sha256 digest for repeatable builds.

`FROM <image> AS <name>`
Name a build stage

`COPY --from=<stage> <src> <dest>`
Copy files out of another stage

`FROM scratch`
Start from an empty image

`FROM --platform=$BUILDPLATFORM <image>`
Run the stage on the build host

`FROM <image>@sha256:<digest>`
Pin a base by digest

`docker build --target <stage> .`
Build only up to one stage

BASE AND STAGES (cont.)

`COPY --from=<image> <src> <dest>`
Copy from an external image

`ARG <name>=<default>`
Before FROM: parametrize the base
A global ARG is only usable in FROM lines. Redeclare it without a value inside a stage to use it there.

BUILD STEPS

`RUN <command>`
Run a command in a new layer

`COPY <src> <dest>`
Copy files from the build context

`COPY --chown=<user>:<group> <src> <dest>`
Copy and set owner

`COPY --chmod=<mode> <src> <dest>`
Copy and set permissions

`COPY --link <src> <dest>`
Copy into an independent layer

`ADD <url> <dest>`
Download a remote file

`ADD <archive>.tar.gz <dest>`
Copy and auto-extract a local tar
For plain files prefer COPY. ADD is for tar auto-extract and URLs.

BUILD STEPS (cont.)

`RUN --mount=type=cache, target=<dir> <command>`
Reuse a package cache between builds

`RUN --mount=type=secret,id=<id> <command>`
Use a secret without baking it in
Read it from /run/secrets/<id>. Pass it with docker build --secret id=<id>,src=<file>.

`RUN a && b && c`
Chain steps in one layer

CONFIGURATION

`ENV <key>=<value>`
Set a variable for build and runtime

`ARG <name>[=<default>]`
Declare a build-time variable
Set with docker build --build-arg <name>=<value>. Not for secrets: values show up in image history.

`WORKDIR <path>`
Set the directory for later steps
Creates the directory if needed. Prefer it over RUN cd.

`USER <user>[:<group>]`
Run later steps as this user

`LABEL <key>=<value>`
Attach image metadata

`RUN useradd -r -u 10001 <user>`
Create an unprivileged user

RUNTIME

`EXPOSE <port>[/tcp|/udp]`
Document a port
This does not publish anything. Use -p or -P at docker run.

`CMD ["exe", "arg"]`
Default command (exec form)

`ENTRYPOINT ["exe"]`
Fixed executable for the container

`CMD ["arg1", "arg2"]`
Default arguments for ENTRYPOINT

`CMD <command> <arg>`
Default command via /bin/sh -c
Shell form runs under sh -c, so signals do not reach your process. Prefix with exec or use exec form.

`VOLUME ["<path>"]`
Declare a mount point

`HEALTHCHECK CMD <command>`
Probe container health

`HEALTHCHECK --start-period=<d> CMD <command>`
Grace time for slow starts

ENTRYPOINT and CMD

Dockerfile	Runs
`CMD ["a"]`	a
`ENTRYPOINT ["e"]`	e
`ENTRYPOINT ["e"] + CMD ["a"]`	e a
`docker run <image> x`	replaces CMD
`docker run --entrypoint <p> <image>`	replaces ENTRYPO

SYNTAX AND CONTEXT

`# syntax=docker/dockerfile:1`
Parser directive: current stable frontend
Must be the very first line of the file.

`RUN <<EOF`
Multi-line script with a heredoc

`<command> \`
Continue a line

`# comment`
Comment line

`docker build -f <file> <context>`
Use another Dockerfile

`docker build -t <name> .`
Build with a tag

`node_modules`
In .dockerignore: skip a path

`**/*.log`
In .dockerignore: match at any depth

`!<pattern>`
In .dockerignore: re-include a match
The last matching line wins, so put exceptions after the pattern they carve out.

Keep .git, node_modules and build output out of the context: it makes builds faster and keeps COPY . from invalidating the cache.

CACHE AND SIZE

Copy dependency manifests first, install, then copy the rest of the source. Code edits then do not re-run the install.

Use a multi-stage build: compile in a fat stage, copy only the artifact into a slim final stage.

Clean package manager caches in the same RUN that created them. A later RUN cannot shrink an earlier layer.

Never put secrets in ARG, ENV or COPY: they stay in the layers. Use RUN --mount=type=secret.

Prefer exec form for CMD and ENTRYPOINT so the process gets SIGTERM from docker stop.

RECIPES

Cache-friendly Node image

```
FROM node:22-slim
WORKDIR /app
COPY package*.json ./
RUN --mount=type=cache,target=/root/.npm npm ci
COPY . .
CMD ["node", "server.js"]
```