dpkg Debian package tool

CONCEPTS

dpkg works on single .deb files and the local database. It does not fetch packages or resolve dependencies: use apt for that.

.deb file ar archive
↓ `--unpack`
Unpacked files placed
↓ `--configure`
Installed maintainer scripts run
↓ `-r`
Removed config kept (rc)
↓ `-P`
Purged config gone

The two-letter state in dpkg -l: ii is installed, rc is removed with config left, hi is installed and held.

INSTALL AND REMOVE

`sudo dpkg -i` *<file.deb>*
Install or upgrade from a file

`sudo dpkg -i` *<dir>***`/*.deb`**
Install several files at once

`sudo dpkg -R` *<dir>*
Install every .deb in a directory

`sudo dpkg -r` *<pkg>*
Remove, keep config files

`sudo dpkg -P` *<pkg>*
Purge: remove with config files

`sudo dpkg --configure -a`
Finish interrupted configuration

`sudo dpkg-reconfigure` *<pkg>*
Rerun a package's configuration questions

Prefer sudo apt install ./<file.deb>: it installs a local file and pulls in dependencies.

QUERY INSTALLED

`dpkg -l`
List all packages

`dpkg -l '`*<pattern>***`'`**
List packages matching a glob

`dpkg -s` *<pkg>*
Show status, version, depends

QUERY INSTALLED (cont.)

`dpkg -L` *<pkg>*
List files owned by a package

`dpkg -S` *<path>*
Find the package owning a file

`dpkg -l | grep ^ii`
Only installed packages

`dpkg -l | grep ^rc`
Removed packages with config left

`dpkg -C`
Audit for half-installed packages

`dpkg -V [`*<pkg>***`]`**
Verify installed files against the database

DPKG-QUERY

`dpkg-query -W` *<pkg>*
Package and version

`dpkg-query -W -f='${Package} ${Version}\n'`
Custom output for all packages

`dpkg-query -W -f='${Installed-Size}\t${Package}\n' | sort -n`
Largest packages last

HOLDS AND SELECTIONS

`echo '`*<pkg>*** `hold' | sudo dpkg --set-selections`**
Hold a package at its version

`echo '`*<pkg>*** `install' | sudo dpkg --set-selections`**
Release a hold

`dpkg --get-selections`
List selections

`dpkg --get-selections | grep hold`
Show held packages

INSPECT .DEB FILES

`dpkg-deb -I` *<file.deb>*
Show control info

`dpkg-deb -c` *<file.deb>*
List contained files

`dpkg-deb -W` *<file.deb>*
Name and version only

`dpkg-deb -x` *<file.deb>* *<dir>*
Extract files without installing