eksctl EKS cluster CLI

START HERE

`eksctl create cluster -f <file>`
Create from config

`eksctl get cluster`
List clusters

`eksctl get nodegroup --cluster <name>`
List node groups


`eksctl scale nodegroup --cluster <name> --name <ng> --nodes <n>`
Resize nodes

`eksctl utils write-kubeconfig --cluster <name>`
Connect kubectl

`eksctl upgrade cluster -f <file> --approve`
Upgrade control plane

`eksctl create cluster --dry-run`
Print generated config

`eksctl delete cluster -f <file> --wait`
Tear it down



What eksctl creates

CONCEPTS

eksctl turns each cluster into CloudFormation stacks; a cluster and each node group are separate stacks you can inspect in AWS.

Pass a ClusterConfig file (-f) instead of long flag lists: it is reviewable, repeatable and works for create, upgrade and delete.

CREATE CLUSTER

`eksctl create cluster`
Default cluster: 2 managed m5.large nodes

`eksctl create cluster -f <file>`
Create from a ClusterConfig file

`--name <name> --region <region>`
Name and region of the cluster

`--version <k8s-version>`
Kubernetes version of the control plane

`--dry-run`
Print the ClusterConfig, create nothing

Options that cannot be written to a config file are rejected together with --dry-run.

`--node-private-networking`
Put nodes in private subnets only

CLUSTERCONFIG FILE

Minimal cluster.yaml

```
apiVersion: eksctl.io/v1alpha5
kind: ClusterConfig
metadata:
  name: <name>
  region: <region>
managedNodeGroups:
  - name: ng-1
    instanceType: m5.large
    desiredCapacity: 3
    minSize: 1
    maxSize: 5
```

`managedNodeGroups: / nodeGroups:`
Managed vs self-managed groups

CLUSTERCONFIG FILE (cont.)

Cluster and node group names: letters, digits and hyphens, starting with a letter, at most 128 characters.

Use eksctl create cluster --dry-run to generate a full config with all defaults filled in, then edit it.

INSPECT CLUSTERS

`eksctl get cluster`
List clusters in the region

`eksctl version`
Show the eksctl version

`eksctl utils nodegroup-health --cluster <name> --name <ng>`
Health issues of a managed group

NODE GROUPS

`eksctl get nodegroup --cluster <name>`
List node groups

`eksctl create nodegroup --cluster <name> --name <ng>`
Add a node group

`eksctl scale nodegroup --cluster <name> --name <ng> --nodes <n>`
Change desired size

`eksctl upgrade nodegroup --cluster <name> --name <ng>`
Roll a managed group to the cluster version

`eksctl delete nodegroup --cluster <name> --name <ng> --approve`
Delete a node group

Without --approve the command only shows a plan.

`--include <glob> / --exclude <glob>`
Select groups when using a config file

KUBECONFIG

`eksctl utils write-kubeconfig --cluster <name>`
Add the cluster to your kubeconfig

create cluster already adds the context to $KUBECONFIG or ~/.kube/config; write-kubeconfig is for a fresh machine or teammate.

UPGRADES

`eksctl upgrade cluster --name <name>`
Preview the control-plane upgrade

`--version <k8s-version> --approve`
Apply the upgrade, one minor step

Only the current version or one minor version higher is allowed.

`eksctl upgrade cluster -f <file> --approve`
Upgrade using metadata.version

`eksctl utils update-kube-proxy --cluster <name> --approve`
Update the kube-proxy add-on

Upgrade order: control plane, then node groups, then the default add-ons.

IAM AND ADD-ONS

`eksctl utils associate-iam-oidc-provider --cluster <name> --approve`
Enable the OIDC provider for IRSA

`eksctl create iamserviceaccount --cluster <name> --name <sa> --namespace <ns> --attach-policy-arn <arn>`
Bind an IAM role to a service account

`eksctl get addon --cluster <name>`
List installed add-ons

IAM AND ADD-ONS (cont.)

`eksctl create addon --cluster <name> --name <addon>`
Install an EKS add-on

`eksctl update addon --cluster <name> --name <addon> --version <ver>`
Change an add-on version

DELETE CLUSTER

`eksctl delete cluster --name <name> --wait`
Delete and report errors

Without --wait only the CloudFormation delete is issued; failures stay hidden.

`eksctl delete cluster -f <file> --wait`
Delete the cluster from its config

Deletion is destructive: load balancers, volumes or ENIs created by workloads can block it. Remove them first, or delete the leftover CloudFormation stacks by hand.

RECIPES

Preview, create, connect

```
eksctl create cluster --name
<name> --region <region> \
  --nodes 3 --dry-run >
cluster.yaml
eksctl create cluster -f
cluster.yaml
kubectl get nodes
```

Upgrade a cluster

```
eksctl upgrade cluster -f
cluster.yaml --approve
eksctl upgrade nodegroup --
cluster <name> --name <ng>
eksctl utils update-kube-proxy
--cluster <name> --approve
```

IRSA for an app

```
eksctl utils associate-iam-oidc-
provider --cluster <name> --
approve
eksctl create iamserviceaccount
--cluster <name> \
  --name <sa> --namespace <ns> \
  --attach-policy-arn
arn:aws:iam::aws:policy/
AmazonS3ReadOnlyAccess \
  --approve
```