Elasticsearch Search and analytics engine

START HERE

`curl -s $ES`
Is it up? Version

`curl -s $ES/_cat/indices?v`
List indices

`curl -s $ES/_cluster/health?pretty`
Cluster status

`curl -X PUT $ES/`*`<index>`*
Create an index

`curl --json '`*`<json>`***`' $ES/`***`<index>`***`/_doc`**
Add a document

`curl -s $ES/`*`<index>`***`/_search?q=`***`<text>`**
Quick search

`curl -s $ES/`*`<index>`***`/`***`<id>`**
Fetch by id

`curl -X DELETE $ES/`*`<index>`*
Delete an index

CONCEPTS

Reading this sheet
Entries are METHOD path. Run them as curl -X <METHOD> $ES/<path>, with --json '<body>' when a body is given (curl 7.82+ sets the JSON headers), or paste them into Kibana Dev Tools. Set ES=localhost:9200 first.

Elasticsearch 8+ enables security by default: use ES=https://localhost:9200 and add -u elastic:<password> --cacert <http_ca.crt> to every curl.

Cluster nodes, one health status
Index mapping + settings
Shard primary + replicas
Document JSON with an _id

Health: green = all shards allocated, yellow = replicas missing, red = a primary is missing.

New documents become searchable after the next refresh (about 1 s by default), not instantly.

CLUSTER AND CAT

`GET /`
Node name, cluster, version

CLUSTER AND CAT (cont.)

`GET _cluster/health?pretty`
Green / yellow / red status

`GET _cat/indices?v`
Indices with docs and size

`GET _cat/nodes?v`
Nodes and load

`GET _cat/shards/`*`<index>`***`?v`**
Where shards live

`GET _cat/indices?v&s=store.size:desc`
Sort cat output by a column

`GET _cat/indices?help`
List cat columns

`GET _cluster/allocation/explain`
Why a shard is unassigned

`GET _nodes/stats`
Per-node statistics

`GET _tasks?detailed`
Running tasks

INDICES

`PUT `*`<index>`**
Create an index
A body may hold settings and mappings.

`DELETE `*`<index>`**
Delete an index and its data

`GET `*`<index>`***`/_mapping`**
Show field mappings

`GET `*`<index>`***`/_settings`**
Show index settings

INDICES (cont.)

`PUT `*`<index>`***`/_mapping`**
Add fields to a mapping
Existing field types cannot change; reindex into a new index instead.

`PUT `*`<index>`***`/_settings`**
Change a dynamic setting

`POST _aliases`
Add or swap aliases atomically

DOCUMENTS

`POST `*`<index>`***`/_doc`**
Index with a generated id

`PUT `*`<index>`***`/_doc/`***`<id>`**
Index or replace by id

`GET `*`<index>`***`/_doc/`***`<id>`**
Get a document

`DELETE `*`<index>`***`/_doc/`***`<id>`**
Delete a document

`POST `*`<index>`***`/_update/`***`<id>`**
Partial update: {"doc":{...}}

`GET `*`<index>`***`/_count`**
Count documents

`POST `*`<index>`***`/_delete_by_query`**
Delete all matching a query

SEARCH

`GET `*`<index>`***`/_search?q=`***`<field>`***`:`***`<text>`**
URI search for quick checks

`POST `*`<index>`***`/_search`**
Search with a query body

SEARCH (cont.)

`{"match": {"`*`<field>`***`": "`***`<text>`***`"}}`**
Full-text match

`{"term": {"`*`<field>`***`": "`***`<value>`***`"}}`**
Exact value (keyword, number)
term does not analyze: on a text field use match, or the .keyword subfield.

`{"bool": {"must": [], "filter": [], "must_not": []}}`
Combine clauses
filter clauses do not score and are cached; use them for yes/no conditions.

`{"range": {"`*`<field>`***`": {"gte": 10, "lt": 20}}}`**
Range filter

`{"exists": {"field": "`*`<field>`***`"}}`**
Field is present

`{"match_phrase": {"`*`<field>`***`": "`***`<text>`***`"}}`**
Exact phrase

`"size": 20, "from": 40`
Paginate

`"sort": [{"`*`<field>`***`": "desc"}]`**
Sort results

`"_source": ["`*`<field>`***`"]`**
Return only some fields

`"pit": {...}, "search_after": [...]`
Deep paging with PIT

AGGREGATIONS

`"size": 0, "aggs": {"by": {"terms": {"field": "`*`<f>`***`"}}}`**
Top values (terms)
Use a keyword field; size 0 skips the hits.

`{"avg": {"field": "`*`<field>`***`"}}`**
Metric: avg, min, max, sum

`{"date_histogram": {"field": "`*`<f>`***`", "calendar_interval": "day"}}`**
Count per day

`{"percentiles": {"field": "`*`<field>`***`"}}`**
Percentiles

`{"cardinality": {"field": "`*`<field>`***`"}}`**
Approximate distinct count

BULK AND REINDEX

`POST _bulk`
Many writes, NDJSON body
Action line, then source line; the body must end with a newline. Send with --data-binary and Content-Type application/x-ndjson.

`POST _reindex`
Copy: {"source":{...},"dest":{...}}
Add ?wait_for_completion=false to run it as a task, then poll GET _tasks/<task_id>.

`GET _tasks/`*`<task_id>`***
Poll a task

RECIPES

Create index, bulk load, search

```
curl -X PUT $ES/books --json
'{"mappings": {"properties":
{"year": {"type":
"integer"}}}}'
curl -X POST "$ES/books/_bulk?
refresh" \
  -H 'Content-Type:
application/x-ndjson' --data-
binary @books.ndjson
curl -s "$ES/books/_search?q=
title:dune&pretty"
```

Swap to a new index behind an alias

```
# alias books → books_v1
curl -X PUT $ES/books_v2 --json
@mapping.json
curl -X POST $ES/_reindex --
json \
  '{"source": {"index":
"books_v1"}, "dest": {"index":
"books_v2"}}'
curl -X POST $ES/_aliases --
json @swap.json
```

Filtered search with a count per genre

```
curl -s $ES/books/_search --
json '{
  "query": {"bool": {"must":
{"match": {"title": "dune"}},
    "filter": {"range":
{"year": {"gte": 1965}}}}},
  "aggs": {"genre": {"terms":
{"field": "genre"}}}}'
```

Pull just the ids with jq

```
curl -s "$ES/books/_search?
size=100" \
  | jq -r '.hits.hits[]._id'
```