Fail2ban Ban brute-force attackers

Log or journal watched by a jail → `filter regex` → **Failure** one match per IP → `maxretry in findtime` → **Ban** action runs → `after bantime` → **Unban** action undoes it

CONCEPTS

A jail ties a log, a filter and an action together; it bans an IP after maxretry failures within findtime.

Edit jail.local or jail.d/*.local, never jail.conf: .local files override it and survive package upgrades.

Fail2ban only reacts to log lines. It is a complement to a firewall, not a replacement.

SERVICE AND CONFIG CHECK

`sudo systemctl enable --now fail2ban`
Start now and at boot

`sudo systemctl status fail2ban`
Check the daemon

`sudo fail2ban-client ping`
Is the server answering?

`sudo fail2ban-client -t`
Test the configuration

`sudo fail2ban-client reload`
Reload all config

SERVICE AND CONFIG CHECK (cont.)

`sudo fail2ban-client reload <jail>`
Reload one jail

STATUS AND BANS

`sudo fail2ban-client status`
List jails

`sudo fail2ban-client status <jail>`
Failed and banned IPs of a jail

`sudo fail2ban-client banned`
All banned IPs, per jail

`sudo fail2ban-client banned <ip>`
Which jails ban this IP?

`sudo fail2ban-client set <jail> banip <ip>`
Ban an IP by hand

`sudo fail2ban-client set <jail> unbanip <ip>`
Unban an IP in a jail

`sudo fail2ban-client unban <ip>`
Unban an IP everywhere

`sudo fail2ban-client unban --all`
Unban every address

JAILS AT RUNTIME

`sudo fail2ban-client start <jail>`
Start a stopped jail

`sudo fail2ban-client stop <jail>`
Stop one jail

`sudo fail2ban-client set <jail> bantime <time>`
Change ban length

`sudo fail2ban-client set <jail> maxretry <n>`
Change failure threshold

`sudo fail2ban-client set <jail> addignoreip <ip>`
Whitelist an IP

CONFIG FILES

`/etc/fail2ban/jail.local`
Your jail overrides

`/etc/fail2ban/filter.d/`
Filters: failregex per service

`[DEFAULT]`
Section for settings every jail inherits

`enabled = true`
Turn a jail on

`bantime = 1h`
Ban length (s, m, h, d, w, mo, y)

CONFIG FILES (cont.)

`findtime = 10m`
Window for counting failures

`maxretry = 5`
Failures allowed before a ban

`ignoreip = 127.0.0.1/8 ::1 <ip>`
Never ban these hosts or CIDRs

`logpath = /var/log/auth.log`
File(s) to watch, globs allowed

`banaction = nftables`
Firewall backend for bans

`bantime.increment = true`
Lengthen bans for repeat offenders

FILTERS AND TESTING

`fail2ban-regex <logfile> <filter-or-regex>`
Test a filter against a log

`fail2ban-regex <logfile> /etc/fail2ban/filter.d/sshd.conf`
Test a filter file

`fail2ban-regex systemd-journal <filter>`
Test against the journal

FILTERS AND TESTING (cont.)

`fail2ban-regex '<log line>' '<regex>'`
Test a single line and regex

`fail2ban-regex --print-all-missed <logfile> <filter>`
Show lines the filter missed

`<HOST>`
Placeholder in failregex that captures the IP

Fail2ban-regex prints counts of matched, missed and ignored lines. Many missed lines that should fail means the regex is wrong.

LOGS

`sudo tail -f /var/log/fail2ban.log`
Follow Fail2ban's own log

`sudo grep Ban /var/log/fail2ban.log`
Find ban events

`sudo fail2ban-client flushlogs`
Reopen log files after rotation