FastAPI Python web APIs

Request path, query, body → validate → **Pydantic** types to values → Depends → **Path function** your code → response_model → **Response** JSON + OpenAPI

CONCEPTS

FastAPI reads your type hints: they decide where a parameter comes from and how it is validated.

Validation failures return 422 automatically; no manual checks needed.

RUN SERVER

fastapi dev
Dev server with reload (auto-detects app)

fastapi dev *<path/to/file.py>*
Run a specific file or package

fastapi run
Production mode, no reload, 0.0.0.0

fastapi dev --port *<port>*
Change the port (default 8000)

fastapi dev --host 0.0.0.0
Listen on all interfaces

fastapi dev --app *<name>*
Pick the app variable in the module

fastapi run --workers *<n>*
Several worker processes

APP AND ROUTES

app = FastAPI(title="<name>**")**
Create the app

@app.get("/")
Handle GET requests

@app.post("/items")
Handle POST requests

@app.put("/items/{item_id}")
Handle PUT requests

@app.delete("/items/{item_id}")
Handle DELETE requests

router = APIRouter(prefix="/items")
Group routes in a module

app.include_router(router)
Mount a router

app.add_middleware(CORSMiddleware, allow_origins=[...])
Enable CORS

PARAMETERS

def f(item_id: int)
Path parameter from {item_id}

def f(skip: int = 0, limit: int = 10)
Query parameters with defaults

PARAMETERS (cont.)

def f(q: str | None = None)
Optional query parameter

q: Annotated[str, Query(max_length=50)]
Validate a query parameter

n: Annotated[int, Path(ge=1)]
Validate a path parameter

tags: Annotated[list[str], Query()]
Repeated query values (?tags=a&tags=b)

x: Annotated[str | None, Header()] = None
Read a request header

name: Annotated[str, Form()]
Read a form field

f: UploadFile
Receive an uploaded file

REQUEST BODY

class Item(BaseModel):
Define a body schema

def f(item: Item)
Parse the JSON body into a model

price: float = Field(gt=0)
Constrain a model field

REQUEST BODY (cont.)

tags: list[str] = []
Field with a default value

item.model_dump()
Model to a dict

item.model_dump(exclude_unset=True)
Only fields the client sent (PATCH)

RESPONSES

@app.get("/x", response_model=Item)
Filter and document the output

@app.post("/x", status_code=201)
Set the success status code

from fastapi import status
Named codes: status.HTTP_201_CREATED

raise HTTPException(status_code=404, detail="...")
Send an error response

DEPENDENCIES

def f(db: Annotated[Session, Depends(get_db)])
Inject a dependency

DEPENDENCIES (cont.)

CommonParams = Annotated[dict, Depends(common)]
Reusable dependency alias

def get_db(): yield db
Dependency with cleanup after the response

app.dependency_overrides[<d>**] =** <f>
Swap a dependency in tests

TESTING AND DOCS

client = TestClient(app)
Test client (needs httpx)

client.get("/items/1")
Call a route in a test

client.post("/items", json={...})
POST a JSON body

assert r.status_code == 200
Check the status

r.json()
Decode the JSON response

/docs
Swagger UI

/openapi.json
OpenAPI schema