FastAPI Python web APIs

CONCEPTS

FastAPI reads your type hints: they decide where a parameter comes from and how it is validated.

Request path, query, body
↓ validate
Pydantic types to values
↓ Depends
Path function your code
↓ response_model
Response JSON + OpenAPI

RUN SERVER

fastapi dev
Dev server with reload (auto-detects app)

fastapi dev *<path/to/file.py>*
Run a specific file or package

fastapi run
Production mode, no reload, 0.0.0.0

fastapi dev --port *<port>*
Change the port (default 8000)

APP AND ROUTES

app = FastAPI(title="*<name>***")**
Create the app

@app.get("/")
Handle GET requests

@app.post("/items")
Handle POST requests

@app.put("/items/{item_id}")
Handle PUT requests

@app.delete("/items/{item_id}")
Handle DELETE requests

router = APIRouter(prefix="/items")
Group routes in a module

app.include_router(router)
Mount a router

PARAMETERS

def f(item_id: int)
Path parameter from {item_id}

def f(skip: int = 0, limit: int = 10)
Query parameters with defaults

PARAMETERS (cont.)

def f(q: str | None = None)
Optional query parameter

q: Annotated[str, Query(max_length=50)]
Validate a query parameter

REQUEST BODY

class Item(BaseModel):
Define a body schema

def f(item: Item)
Parse the JSON body into a model

price: float = Field(gt=0)
Constrain a model field

item.model_dump()
Model to a dict

RESPONSES

@app.get("/x", response_model=Item)
Filter and document the output

@app.post("/x", status_code=201)
Set the success status code

raise HTTPException(status_code=404, detail="...")
Send an error response

DEPENDENCIES

def f(db: Annotated[Session, Depends(get_db)])
Inject a dependency

TESTING AND DOCS

client = TestClient(app)
Test client (needs httpx)

client.get("/items/1")
Call a route in a test

client.post("/items", json={...})
POST a JSON body

assert r.status_code == 200
Check the status

r.json()
Decode the JSON response

/docs
Swagger UI