Flatpak Sandboxed Linux apps

START HERE

`flatpak` **`search`** *`<text>`*
Find an app

`flatpak` **`uninstall --unused`**
Remove unused runtimes

`flatpak` **`install`** *`<remote>`* *`<app-id>`*
Install an app

`flatpak` **`info`** *`<app-id>`*
Details of an app

`flatpak` **`run`** *`<app-id>`*
Start an app

`flatpak` **`list`**
What is installed

`flatpak` **`update`**
Update everything

`flatpak` **`uninstall`** *`<app-id>`*
Remove an app

Remote e.g. flathub → `install` → **Installation** --user or --system → `run` → **Sandbox** app + runtime → `override` → **Permissions** per app or global

CONCEPTS

Apps run in a sandbox on a shared runtime. Installing one app may pull in a runtime that other apps reuse.

A ref is name/arch/branch, e.g. org.mozilla.firefox/x86_64/stable. The short app ID is usually enough.

Install without --user or --system defaults to system-wide and may ask for admin rights. Use --user for a per-user install.

REMOTES

`flatpak` **`remotes`**
List configured remotes

`flatpak` **`remote-add --if-not-exists`** *`<name>`* *`<url-or-.flatpakrepo>`*
Add a remote

`flatpak` **`remote-ls`** *`<remote>`*
List what a remote offers

REMOTES (cont.)

`flatpak` **`remote-delete`** *`<remote>`*
Remove a remote

INSTALL AND UPDATE

`flatpak` **`search`** *`<text>`*
Search remotes for apps

`flatpak` **`install`** *`<remote>`* *`<app-id>`*
Install from a remote

`flatpak` **`install --user`** *`<app-id>`*
Install for the current user only

`flatpak` **`install -y`** *`<app-id>`*
Install without prompts

`flatpak` **`update`**
Update apps and runtimes

`flatpak` **`update`** *`<app-id>`*
Update one app

INSTALL AND UPDATE (cont.)

`flatpak` **`update --commit=`***`<commit>`* *`<app-id>`*
Move to a specific commit

Find commits with remote-info --log; mask the ref afterwards or the next update moves it again.

`flatpak` **`uninstall`** *`<app-id>`*
Remove an app

`flatpak` **`uninstall --unused`**
Remove unused runtimes

`flatpak` **`uninstall --delete-data`** *`<app-id>`*
Remove app and its data

`flatpak` **`mask`** *`<pattern>`*
Block updates for matches

`flatpak` **`pin`** *`<runtime>`*
Keep a runtime from auto-removal

RUNNING

`flatpak` **`run`** *`<app-id>`*
Start an app

RUNNING (cont.)

`flatpak` **`run --command=`***`<cmd>`* *`<app-id>`*
Run another command in the sandbox

`flatpak` **`run --filesystem=`***`<path>`* *`<app-id>`*
Grant a path for this run

`flatpak` **`ps`**
List running instances

`flatpak` **`kill`** *`<app-id>`*
Stop a running app

INSPECT

`flatpak` **`list`**
List installed apps and runtimes

`flatpak` **`list --app`**
List only apps

`flatpak` **`list --runtime`**
List only runtimes

`flatpak` **`info`** *`<app-id>`*
Show an installed app

INSPECT (cont.)

`flatpak` **`info -m`** *`<app-id>`*
Show its metadata and permissions

`flatpak` **`history`**
Show install and update history

PERMISSIONS

`flatpak` **`override --user --filesystem=`***`<path>`* *`<app-id>`*
Give an app a path

`flatpak` **`override --user --socket=`***`<socket>`* *`<app-id>`*
Allow a socket, e.g. wayland

`flatpak` **`override --user --nosocket=`***`<socket>`* *`<app-id>`*
Deny a socket

`flatpak` **`override --user --env=`***`<VAR>=<value>`* *`<app-id>`*
Set an env var

`flatpak` **`override --user --show`** *`<app-id>`*
Show your overrides

`flatpak` **`override --user --reset`** *`<app-id>`*
Clear your overrides

MAINTENANCE

`flatpak` **`repair --user`**
Check and fix the user install

RECIPES

Set up Flathub and install

```
flatpak remote-add --if-not-exists flathub \
  https://dl.flathub.org/repo/flathub.flatpakrepo
flatpak install flathub org.mozilla.firefox
flatpak run org.mozilla.firefox
```

Tidy up

```
flatpak update
flatpak uninstall --unused
flatpak repair --user
```

Let one app see a folder

```
flatpak override --user --filesystem=$HOME/Projects <app-id>
flatpak override --user --show <app-id>
flatpak override --user --reset <app-id>
```

Hang app? Stop it

```
flatpak ps
flatpak kill <app-id>
```