Flyway Database migrations

CONCEPTS

Never edit a migration that has been applied: its checksum is stored and validate will fail. Add a new one instead.

V1__init.sql files in locations
↓ `flyway migrate`
Target DB your schema
↓ records
Schema history
flyway_schema_history
↓ checked by
validate checksums + order

Versioned migrations run once in version order; repeatable ones (R__) rerun whenever their checksum changes, after all versioned ones.

Undo migrations, check -dryrun and check -drift/-changes need paid editions; clean, check -code and the rest here are in Community.

MIGRATION FILES

V<n>__<desc>.sql
Versioned migration (runs once)

R__<desc>.sql
Repeatable migration

U<n>__<desc>.sql
Undo migration for a version

`flyway` **add -description=**<text>
Create next versioned script

`flyway` **add -version=**<v> **-description=**<text>
Create script with explicit version

${<name>**}**
Placeholder inside SQL

-locations=filesystem:<dir>
Where to scan for scripts

PROJECT AND SETUP

`flyway` **init -projectName=**<name> **-databaseType=**<type>
Generate project and flyway.toml

`flyway` **-v**
Print version

PROJECT AND SETUP (cont.)

`flyway` **-environment=**<env>
Pick the target environment

`flyway` **-configFiles=**<file>
Use a specific config file

`flyway` **-url="**<jdbc-url>**" -user=**<u> **-password=**<p> **migrate**
Connect without a config file

-schemas=<a>**,**<b>
Schemas Flyway manages

MIGRATE AND INSPECT

`flyway` **migrate**
Apply all pending migrations

`flyway` **info**
Show applied and pending

`flyway` **validate**
Compare files with history

`flyway` **migrate -target=**<version>
Stop at a version

`flyway` **migrate -outOfOrder=true**
Allow lower versions after higher

`flyway` **migrate -baselineOnMigrate=true**
Baseline a non-empty DB on first run

`flyway` **info -infoOfState=pending**
Filter by state

`flyway` **undo**
Undo the last versioned migration

REPAIR AND RECOVER

`flyway` **repair**
Remove failed rows, realign checksums

`flyway` **baseline**
Mark existing DB as migrated

`flyway` **baseline -baselineVersion=**<v>
Baseline at a version

`flyway` **clean -cleanDisabled=false**
Drop all objects in schemas

REPAIR AND RECOVER (cont.)

After a failed migration run repair, fix the script, then migrate again.

Keep cleanDisabled=true outside dev and test environments.

`flyway` **check -code**
Review migrations with code analysis

CONFIGURATION

flyway.toml
Project config file

[environments.<name>**] url, user, password**
Define an environment

[flyway] locations = ["filesystem:sql"]
Flyway settings in TOML

FLYWAY_URL / FLYWAY_USER / FLYWAY_PASSWORD
Env var overrides

locations
Folders scanned recursively

connectRetries
Retry connecting to the DB

[flyway.placeholders] name = "value"
Define placeholders

beforeMigrate.sql / afterMigrate.sql
Callback scripts in locations

-X
Debug output

-outputType=json
Machine-readable output

RECIPES

First migration

```
flyway init -projectName=app -
databaseType=PostgreSql
flyway add -
description=create_users
# edit the new file in sql/
flyway info
flyway migrate
```