fx JSON viewer and processor

CONCEPTS

> Every argument is a JavaScript function; the result of one is the input x of the next. Start with . to skip x ⇒ x.

Input file or stdin
↓ parse
Arg 1 .users
↓ x
Arg 2 @.name
↓ x
Output JSON or text

Each argument gets the previous result as x

RUN AND INPUT

fx *<file>*
Open a file interactively

<cmd> **| fx**
Open piped JSON interactively

fx *<file>* *<expr>*
Apply an expression, print result

<cmd> **| fx .**
Pretty-print stdin

fx *<file>* *<expr1>* *<expr2>*
Chain expressions

EXPRESSIONS

.*<key>*
Select a field

.*<key>***[0]**
Select an array element

x ⇒ x.*<key>*
Explicit arrow function

'.map(x ⇒ x.*<key>***)'**
Map over an array in JS

'.filter(x ⇒ x.*<key>* **> 1)'**
Filter an array in JS

@.*<key>*
Shorthand for map

?.*<key>*
Shorthand for filter

BUILT-IN FUNCTIONS

len
Length of array, string or object

keys / values
Object keys or values

FORMATS

--yaml
Read YAML

INTERACTIVE: MOVE

Arrows
Move; h j k l also work

g / **G**
Top / bottom

@
Fuzzy-search a path and jump

q
Quit

INTERACTIVE: FOLD AND VIEW

Enter / **l**
Expand node

Backspace / **h**
Collapse node

?
Show help

INTERACTIVE: SEARCH AND OUTPUT

.
Open query input

/
Regex search

n / **N**
Next / previous match

P
Print value to stdout and exit