GCC C/C++ compiler

CONCEPTS

gcc drives four stages: preprocess, compile, assemble, link. -E, -S and -c stop after the first three.

x.c source
↓ -E
x.i preprocessed
↓ -S
x.s assembly
↓ -c
x.o object
↓ link
a.out executable

Each stage has a flag that stops after it

Put libraries (-l) after the files that use them: the linker resolves symbols left to right.

COMPILE AND LINK

gcc *<file.c>* **-o** *<out>*
Build an executable

gcc -c *<file.c>*
Compile to an object file

gcc *<a.o>* *<b.o>* **-o** *<out>*
Link objects together

LANGUAGE STANDARD

gcc -std=c17 *<file.c>*
Pick the C standard

WARNINGS

gcc -Wall *<file.c>*
Common warnings

gcc -Wextra *<file.c>*
Extra warnings on top of -Wall

gcc -Werror *<file.c>*
Treat warnings as errors

OPTIMIZATION

gcc -O2 *<file.c>*
Standard release optimization

DEBUG AND PROFILE

gcc -g *<file.c>*
Add debug info for gdb

SANITIZERS

gcc -fsanitize=address -g *<file.c>*
AddressSanitizer: memory errors

gcc -fsanitize=undefined -g *<file.c>*
UBSan: undefined behavior

INCLUDE AND LINK PATHS

gcc -I<*dir*> *<file.c>*
Add a header search dir

gcc -L<*dir*> *<file.c>* **-l**<*name*>
Add a library search dir

gcc *<file.c>* **-l**<*name*>
Link libname.so or libname.a

gcc *<file.c>* **-lm**
Link the math library

gcc -pthread *<file.c>*
Enable POSIX threads

MACROS

gcc -D<*name*> *<file.c>*
Define a macro as 1

gcc -D<*name*>**=**<*value*> *<file.c>*
Define a macro with a value

DEPENDENCIES AND LIBRARIES

gcc -MMD -MP -c *<file.c>*
Write .d dependency file with build

gcc -fPIC -c *<file.c>*
Position-independent object

gcc -shared -o lib<*name*>**.so** *<a.o>*
Build a shared library

INSPECT THE COMPILER

gcc --version
Show the GCC version