gcloud CLI Google Cloud CLI

CONCEPTS

Commands read as gcloud <product> <resource> <verb>, e.g. compute instances list. Add --help at any level to explore.

Account who you are
↓ `auth login`
Configuration project, region, zone
↓ `config set`
Command gcloud compute ...
↓ `--project`
Resource VM, bucket, role

Most commands need a project. Set a default once, or override per call with --project.

Credentials from gcloud auth login are not used by client libraries; use application-default login for those.

AUTH AND ACCOUNTS

`gcloud auth login`
Sign in via browser

`gcloud auth list`
Show credentialed accounts

`gcloud auth application-default login`
Credentials for local code and SDKs

CONFIG AND PROJECTS

`gcloud config list`
Show active properties

`gcloud config set project <id>`
Set default project

`gcloud config set compute/zone <zone>`
Set default zone

`gcloud config configurations list`
List named configurations

`gcloud config configurations activate <name>`
Switch configuration

`gcloud projects list`
List projects you can see

CONFIG AND PROJECTS (cont.)

`gcloud services enable <api>.googleapis.com`
Enable an API

COMPUTE INSTANCES

`gcloud compute instances list`
List VMs

`gcloud compute instances create <vm>`
Create a VM

`gcloud compute instances start <vm>`
Start a VM

`gcloud compute instances stop <vm>`
Stop a VM

`gcloud compute instances delete <vm>`
Delete a VM

SSH AND COPY

`gcloud compute ssh <vm>`
SSH into a VM

`gcloud compute ssh <vm> --command="<cmd>"`
Run one command remotely

`gcloud compute ssh <vm> --tunnel-through-iap`
SSH without a public IP

`gcloud compute scp <file> <vm>:<path>`
Copy a file to a VM

STORAGE

`gcloud storage ls`
List buckets

`gcloud storage ls gs://<bucket>/<prefix>`
List objects

`gcloud storage cp <src> <dst>`
Copy files to, from or between buckets

`gcloud storage cp -r <dir> gs://<bucket>`
Upload a directory

`gcloud storage mv <src> <dst>`
Move or rename objects

STORAGE (cont.)

`gcloud storage rsync -r <src> <dst>`
Sync a directory with a bucket

`gcloud storage buckets create gs://<bucket> --location=<loc>`
Create a bucket

IAM

`gcloud projects get-iam-policy <project>`
Show who has which role

`gcloud projects add-iam-policy-binding <project> --member=<member> --role=<role>`
Grant a role

FORMAT AND FILTER

`--format=json`
Output as JSON

`--format="value(<field>)"`
Print bare values for scripts

`--format="table(<f1>, <f2>)"`
Choose table columns

`--filter="<field>=<value>"`
Keep matching rows

`--project=<id>`
Override the project for one call

HELP AND DISCOVERY

`gcloud <group> --help`
List subcommands in a group

RECIPES

Separate work and personal setups

```
gcloud config configurations
create work
gcloud config set project <work-
project>
gcloud config set account
<you@work.com>
gcloud config configurations
activate default
```

Script-friendly VM IPs

```
gcloud compute instances list \
  --filter="status=RUNNING" \
  --format="value(name,
networkInterfaces[0].
accessConfigs[0].natIP)"
```