GitLab CI/CD Pipelines in YAML

CONCEPTS

> Everything lives in .gitlab-ci.yml at the repo root; a push or merge request creates a pipeline of stages, each holding parallel jobs.

Pipeline one per push, MR or schedule

Stage runs in order; next waits for all jobs

Job script run by a runner in a clean checkout

JOBS

```
<job>:
  script:
    - <cmd>
```
Minimal job

`stage: <name>`
Put the job in a stage

`image: <name>:<tag>`
Container image for the job

`before_script: [<cmd>]`
Run before script

`after_script: [<cmd>]`
Run after, even on failure

`services: [postgres:16]`
Sidecar containers (databases)

`tags: [<runner-tag>]`
Choose runners by tag

`when: manual`
Wait for a click to run

STAGES AND ORDER

`stages: [build, test, deploy]`
Set stage order

`needs: [<job>]`
Start once these jobs finish

RULES

`rules: - if: $CI_COMMIT_BRANCH == "main"`
Run when the expression is true

RULES (cont.)

`rules: - if: $CI_PIPELINE_SOURCE == "merge_request_event"`
Run in merge request pipelines

`rules: - changes: ["src/**"]`
Run when these files changed

`rules: - when: never`
Fallback: skip the job

```
workflow:
  rules: [...]
```
Decide whether a pipeline exists

ARTIFACTS AND CACHE

```
artifacts:
  paths: [<path>]
```
Keep files after the job

`artifacts: reports: junit: <file>`
Show test results in the MR

```
cache:
  paths: [<dir>]
```
Reuse files between runs

`cache: key: $CI_COMMIT_REF_SLUG`
One cache per branch

REUSE AND INCLUDE

`include: - local: <path>`
Include a file from this repo

```
<job>:
  extends: .<template>
```
Inherit from a hidden job

`.<name>:`
Hidden job: a template, never runs

VARIABLES AND ENVIRONMENTS

```
variables:
  <NAME>: <value>
```
Pipeline or job variable

`$CI_COMMIT_BRANCH`
Branch name