Gitleaks Secret scanner

CONCEPTS

Exit code 1 means leaks were found, 0 means clean. That is what makes it usable as a CI or hook gate.

Source git history, directory, stdin
↓ match
Rules default or .gitleaks.toml
↓ filter
Allowlists paths, regexes, baseline, allow comments
↓ report
Findings log, json, sarif, csv, junit

detect and protect are deprecated since v8.19.0 and hidden from --help. Use git, dir and stdin instead.

SCAN MODES

gitleaks git
Scan commit history of the current repo

gitleaks git *<repo-path>*
Scan another repository

gitleaks dir *<path>*
Scan a folder or single file

cat *<file>* **| gitleaks stdin**
Scan piped data

gitleaks git --log-opts="*<opts>***"**
Pass git log options to limit commits

gitleaks git --log-opts="--all"
Include all branches and tags

-v / --verbose
Print each finding in detail

gitleaks version
Show the installed version

REPORTS

-r *<file>*
Write findings to a report file

-f json / csv / junit / sarif
Choose the report format

--redact
Mask secrets in logs and stdout

--exit-code *<n>*
Exit code to use when leaks are found

REPORTS (cont.)

--no-banner
Hide the ASCII banner

--no-color
Plain output for logs

BASELINE AND IGNORES

gitleaks git -r baseline.json
Create a baseline from today's findings

-b *<baseline.json>*
Report only findings not in the baseline

// gitleaks:allow
Comment on a line to skip its findings

.gitleaksignore
Repo file listing finding fingerprints to skip

CONFIGURATION

-c *<file>*
Use this config file

.gitleaks.toml
Config picked up from the scan target

GITLEAKS_CONFIG=*<file>*
Config path via environment

--enable-rule *<id>*
Run only the given rule IDs

[extend] useDefault = true
Keep default rules and add your own

[extend] disabledRules = ["*<id>***"]**
Turn off inherited rules

[[rules]] id, regex, keywords
Define a custom detection rule

ALLOWLISTS

[[allowlists]]
Global allowlist block

paths = ['''*<regex>***''']**
Skip files by path regex

regexes = ['''*<regex>***''']**
Skip findings matching a regex

commits = ["*<sha>***"]**
Skip findings in given commits

ALLOWLISTS (cont.)

[[rules.allowlists]]
Allowlist for a single rule

SCANNING OPTIONS

-l *<level>*
Log level: trace to fatal

HOOKS AND CI

repo: https://github.com/gitleaks/gitleaks
pre-commit repo entry; pin rev, id: gitleaks

pre-commit install
Activate the hook in this clone

pre-commit autoupdate
Bump the pinned gitleaks rev

SKIP=gitleaks git commit
Skip the hook once

gitleaks/gitleaks-action
GitHub Action that runs the scan

docker run -v *<dir>***:/path ghcr.io/gitleaks/gitleaks:latest git /path**
Run in Docker

brew install gitleaks
Install on macOS or Linuxbrew

RECIPES

Scan history and keep a redacted report

```
gitleaks git --redact -v \
  -f json -r gitleaks-report.json
```

Adopt on an old repo: baseline first, gate new leaks

```
gitleaks git -r baseline.json || true
gitleaks git -b baseline.json -r new.json
```

Custom rule on top of the defaults (.gitleaks.toml)

```
[extend]
useDefault = true

[[rules]]
id = "acme-token"
regex = '''acme_[a-z0-9]{32}'''
keywords = ["acme_"]
```

Allowlist test fixtures and docs (.gitleaks.toml)

```
[[allowlists]]
description = "fixtures"
paths = ['''testdata/.*''',
'''docs/.*\.md''']
```