Gleam Typed BEAM and JS language

CONCEPTS

Gleam compiles to Erlang (BEAM) or JavaScript. The target comes from gleam.toml, else Erlang, and --target overrides it.

src/*.gleam your modules
↓ `gleam build`
build/ BEAM files or JS
↓ `gleam run`
main() entry point
From source to running code

Tests live in test/ and gleam test runs main in <package>_test; dev code goes in dev/ with gleam dev.

PROJECTS

`gleam new <dir>`
Create a new package

`gleam run`
Compile and run main

`gleam run --target javascript`
Run on the JS target

`gleam run --runtime <rt>`
JS runtime: nodejs, deno or bun

BUILD & CHECK

`gleam build`
Compile package and dependencies

`gleam build --target <t>`
Pick erlang or javascript

`gleam check`
Type-check without code generation

TEST & FORMAT

`gleam test`
Run main of <package>_test

`gleam format`
Format the project

`gleam format --check`
Fail if a file is unformatted

DEPENDENCIES

`gleam add <pkg>`
Add latest compatible version

`gleam add <pkg>@<version>`
Pin a major or full version

`gleam add --dev <pkg>`
Add as a dev dependency

`gleam remove <pkg>`
Remove a dependency

`gleam deps update [<pkg>...]`
Upgrade within gleam.toml limits

SYNTAX BASICS

`let x = 1`
Immutable binding

`x |> f |> g`
Pipe into the first argument

`case v { 0 -> a  _ -> b }`
Exhaustive pattern match

`[first, ..rest]`
List pattern or prepend

`pub type T { A(n: Int)  B }`
Custom type with variants

`Person(..p, age: 30)`
Record update

`use x <- result.try(f())`
Flatten callbacks

`Ok(v) / Error(e)`
Result variants

`import gleam/io.{println}`
Import module and items

HELP

`gleam help`
List all commands

`gleam help <command>`
Help for one command

`gleam --version`
Print the compiler version