goose Database migrations

CONCEPTS

> Set GOOSE_DRIVER, GOOSE_DBSTRING and GOOSE_MIGRATION_DIR (or a .env file) and drop the driver and dbstring from every command.

create new .sql file
↓ edit
Up / Down SQL annotations
↓ goose up
Database goose_db_version
↓ goose status
Verified applied list

CONNECT

`goose <driver> <dbstring> <command>`
Full invocation form

`goose -dir <path> <command>`
Migration directory (default .)

`export GOOSE_DRIVER=<driver>`
Driver from environment

`export GOOSE_DBSTRING=<dbstring>`
Connection string from environment

DBSTRING EXAMPLES

Driver and connection string

driver	dbstring
sqlite3	./app.db
postgres	"user=postgres dbname=app sslmode=disable"
mysql	"user:pass@/app?parseTime=true"
mssql	"sqlserver://user:pass@host:1433?database=app"
clickhouse	"tcp://127.0.0.1:9000"
redshift	"postgres://user:pass@host:5439/db"

CREATE

`goose create <name> sql`
New SQL migration

CREATE (cont.)

`goose -dir <path> create <name> sql`
Create in a given directory

`goose validate`
Check files without running them

SQL ANNOTATIONS

`-- +goose Up`
Start of forward statements

`-- +goose Down`
Start of rollback statements

`-- +goose NO TRANSACTION`
Run outside a transaction (file top)

`-- +goose StatementBegin`
Open a block with inner semicolons

MIGRATE

`goose up`
Apply all pending migrations

`goose up-by-one`
Apply just the next one

`goose up-to <version>`
Migrate up to a version

`goose down`
Roll back the latest one

`goose down-to <version>`
Roll back to a version

`goose redo`
Re-run the latest migration

INSPECT

`goose status`
List migrations and applied time

`goose version`
Print current DB version

INSTALL

`go install github.com/pressly/goose/v3/cmd/goose@latest`
Install with Go