Graphviz Graphs from text

CONCEPTS

Edges use → in digraph and -- in graph; mixing them is a syntax error.

DOT text .gv / .dot
↓ dot
Layout positions
↓ -T<fmt>
Output svg, png, pdf

Pick the engine by graph shape: dot for hierarchies, neato/fdp for networks, circo for rings.

Quote any ID with spaces or dashes: "my node". Keywords like node or edge need quotes too.

COMMAND LINE

dot -T*<fmt>* *<file>* **-o** *<out>*
Render with an explicit format

dot -Tsvg *<file>* **>** *<out>***.svg**
Render SVG to stdout redirect

dot -Kneato -Tpng *<file>* **-o** *<out>*
Choose layout engine by name

GRAPH BASICS

digraph G { ... }
Directed graph body

a → b → c
Chain of edges

a → {b c d}
One source, many targets

a [label="Name"]
Node with display text

a → b [label="x"]
Edge with a label

"two words"
Quote IDs with spaces

label="line1\nline2"
Line break in a label

GRAPH BASICS (cont.)

node [shape=box]
Set node defaults from here on

NODES

shape=box
Rectangle node

shape=circle / diamond
Circle or decision diamond

style=filled fillcolor=*<c>*
Fill node colour

EDGES

style=dashed / dotted
Line style

constraint=false
Edge ignored for ranking

LAYOUT AND GROUPS

rankdir=LR
Left to right (TB default)

{rank=same; a; b}
Put nodes on one rank

subgraph cluster_*<n>* **{ ... }**
Box group; name must start cluster

nodesep=*<in>* **ranksep=***<in>*
Spacing between nodes and ranks

Layout engines

Engine	Best for
dot	Layered hierarchies, flows
neato	Spring model, small graphs
fdp	Springs with clusters
sfdp	Very large graphs
circo	Circular layouts
twopi	Radial from a root

COLOURS AND LABELS

color="#rrggbb"
Hex colour

label=<bold>
HTML-like label