IPython Interactive Python shell

In[n] your input → runs **Out[n]** result → saved as **_ __ ___** last 3 outputs

CONCEPTS

Magics start with % (line) or %% (cell). With automagic on, the % may be left off.

Install with pip install ipython and start it with ipython.

HELP AND INSPECTION

`<obj>?`
Show docs for an object

`<obj>??`
Show source code too

`<obj>.<TAB>`
Complete attributes and methods

`*<pattern>*?`
Search names by wildcard

`%psource <obj>`
Print an object's source

`%<magic>?`
Docs for one magic

RUNNING CODE

`%run <script.py> <args>`
Run a script in this session

`%load <file>`
Load code into the prompt

RUNNING CODE (cont.)

`%edit`
Compose input in your editor

`%paste`
Paste clipboard code as-is

`%cpaste`
Paste block, end with --

`%%writefile <file>`
Write the cell to a file

`%reset`
Clear all variables

TIMING

`%time <stmt>`
Time one run

`%timeit <stmt>`
Time many runs, average

`%%time`
Time the whole cell

`%%timeit`
Time a cell, with setup line

HISTORY AND OUTPUT

`%history`
Show session input

`%history -n`
Include line numbers

HISTORY AND OUTPUT (cont.)

`%history -g <text>`
Search all stored history

`%rerun`
Re-run the previous line

`In[<n>]`
Input of cell n

`Out[<n>]`
Output of cell n

`_ / __ / ___`
Last three outputs

SHELL AND SYSTEM

`!<command>`
Run a shell command

`<var> = !<command>`
Capture output as a list

`!<command> {<pyvar>}`
Insert a Python value

`%%bash`
Run the cell in bash

`%cd <dir>`
Change directory

`%pwd`
Print working directory

`%env <VAR>=<value>`
Set an env variable

`%pip install <pkg>`
Install into this environment

DEBUGGING

`%debug`
Open pdb after an exception

`%pdb on`
Debug every uncaught error

`%xmode Verbose`
Richer tracebacks

`%tb`
Show last traceback again

MODULES AND WORKSPACE

`%load_ext autoreload`
Enable the extension

`%autoreload 2`
Reload all before each run

`%autoreload 1`
Reload only %aimport modules

`%who`
List variable names

`%whos`
List variables with types

`%matplotlib inline`
Plot inside the frontend

CONFIG AND SHORTCUTS

`ipython profile create`
Create default config files

CONFIG AND SHORTCUTS (cont.)

`ipython --profile=<name>`
Start with a profile

`ipython -i <script.py>`
Run, then stay interactive

Keyboard

Key	Does
`Tab`	Complete or cycle
`Ctrl+R`	Search history
`Ctrl+O`	Open new line
`Esc Enter`	Force run block
`Ctrl+L`	Clear screen
`Ctrl+D`	Exit

Startup scripts: put .py or .ipy files in ~/.ipython/profile_default/startup/; they run in filename order.

RECIPES

Edit a module and keep going

```
%load_ext autoreload
%autoreload 2
import mymod
mymod.run()
# edit mymod.py, then call again
```

Debug a failing script

```
%run script.py
%debug
# or start under pdb from the top:
%run -d script.py
```