jc CLI output to JSON

CONCEPTS

> jc only converts text to JSON; it does not filter. Pair it with jq. Most parsers return an array of objects, but some (like uptime) return one object, so check the schema with jc -h --<parser>.

Command output ps, dig, ls, ...
↓ text
jc --<parser> or magic
↓ JSON
jq / script filter, select, format
jc sits between text tools and JSON tools

RUNNING JC

`jc <command> [args]`
Magic syntax: run and parse in one step

`<command> | jc --<parser>`
Standard syntax: parse piped text

`cat <file> | jc --<parser>`
Parse a saved file or capture

`jc <start>:<end> --<parser>`
Parse only a slice of input lines

`jc dig <host> | jq -r '.[].answer[].data'`
Magic syntax feeding jq

`ps aux | jc --ps`
Same, with the standard syntax

OUTPUT OPTIONS

`jc -p <command>`
Pretty-print JSON

`jc -y <command>`
YAML output

`jc -r <command>`
Raw output: strings, no int or date conversion

`jc -M <command>`
Add _jc_meta: parser, timestamp, exit code

OUTPUT OPTIONS (cont.)

`jc -d <command>`
Debug a parse failure (-dd verbose)

COMMON PARSERS

`jc ps aux`
Processes (--ps)

`jc ls -l <dir>`
Directory listing (--ls)

`jc df -h`
Disk usage per filesystem (--df)

`jc dig <host>`
DNS answers and timings (--dig)

`jc ss -tulpn`
Sockets (--ss)

`jc ip route`
Routing table (--ip-route)

`jc lsblk`
Block devices as a tree (--lsblk)

`jc systemctl list-units`
Units and their state (--systemctl)

`jc stat <file>`
File metadata (--stat)

`jc free`
Memory use (--free)

FILE AND STRING PARSERS

`jc --csv < <file>.csv`
CSV rows to objects

`jc --asciitable < <table>.txt`
Any aligned text table to JSON

STREAMING AND HELP

`<command> | jc --<parser>-s`
Streaming parser: one JSON line per input line

`jc -h`
List parsers

`jc -h --<parser>`
Parser docs, schema and examples