Jest JavaScript test runner

Find tests testMatch → transform → **Run in workers** per file → expect → **Report** results, coverage

CONCEPTS

Through npm, put -- before flags: npm test -- -t "login". Flags override the config file.

RUN TESTS

`npx jest`
Run every test

`npx jest <pattern>`
Run test files matching a regex

`npx jest -t "<name>"`
Run tests whose name matches

`npx jest --watch`
Rerun tests related to changes

`npx jest --watchAll`
Rerun all tests on any change

`npx jest --onlyChanged`
Only tests for uncommitted changes

`npx jest --bail`
Stop after the first failing suite

OUTPUT AND SPEED

`npx jest --coverage`
Collect and print coverage

OUTPUT AND SPEED (cont.)

`npx jest --verbose`
List every test with its result

`npx jest --ci`
Never write new snapshots

`npx jest --runInBand`
Run serially in one process

`npx jest --maxWorkers=<n>`
Limit parallel workers (n or 50%)

SNAPSHOTS

`npx jest -u`
Re-record failing snapshots

`npx jest -u -t "<name>"`
Update snapshots of matching tests only

`expect(<value>).toMatchSnapshot()`
Compare against a stored snapshot

WRITING TESTS

`test("<name>", () => { ... })`
Define a test (alias: it)

`describe("<name>", () => { ... })`
Group tests

WRITING TESTS (cont.)

`test.only("<name>", fn)`
Run only this test in the file

`test.skip("<name>", fn)`
Skip this test

`test.each([[a, b], ...])("<name>", fn)`
Run one test per table row

`beforeEach(fn) / afterEach(fn)`
Run before or after every test

`expect(<value>).toBe(<x>)`
Strict equality (Object.is)

`expect(<value>).toEqual(<x>)`
Deep equality

`expect(<value>).toContain(<x>)`
Array item or substring

`expect(<fn>).toThrow(<msg>)`
Function throws

`await expect(<promise>).resolves.toBe(<x>)`
Assert on a resolved promise

`await expect(<promise>).rejects.toThrow()`
Assert on a rejected promise

WRITING TESTS (cont.)

Async tests must return or await the promise, or Jest finishes before the assertions run.

MOCKS

`jest.fn()`
Create a mock function

`jest.spyOn(<obj>, "<method>")`
Spy on a method, keep the original

`jest.mock("<module>")`
Auto-mock a module (hoisted)

`jest.mock("<module>", () => ({...}))`
Mock a module with a factory

`mockFn.mockReturnValue(<x>)`
Always return x

`mockFn.mockResolvedValue(<x>)`
Return a promise resolving to x

`mockFn.mockImplementation(<fn>)`
Set the implementation

MOCKS (cont.)

`toHaveBeenCalledWith(<args>)`
Assert on call arguments

`expect(mockFn).toHaveBeenCalledTimes(<n>)`
Assert on call count

`jest.useFakeTimers()`
Fake setTimeout and friends

`jest.advanceTimersByTime(<ms>)`
Move fake time forward

CONFIG

`testEnvironment: "jsdom"`
Browser-like DOM (needs jest-environment-jsdom)

RECIPES

Debug one failing test

```
npx jest path/to/file.test.js -t "<name>" --runInBand
# attach a debugger:
node --inspect-brk node_modules/.bin/jest --runInBand
```

Pre-commit: test what you changed

```
npx jest --bail --findRelatedTests src/a.js src/b.js
```