Jujutsu Git-compatible version control

Edit files amends @ → `jj describe` → **Describe** set the message → `jj new` → **New change** fresh empty @ → `jj bookmark set` → **Bookmark** branch pointer → `jj git push` → **Remote** origin

CONCEPTS

There is no staging area: the working copy is itself a commit (@), and file edits amend it automatically.

Change IDs (letters) stay stable when a change is rewritten; commit IDs (hex) change. Use change IDs.

Bookmarks do not follow @ automatically: move them with jj bookmark set before pushing.

SETUP

jj git clone *<url>*
Clone a Git repository

jj git init --colocate
Use jj in an existing Git repo

jj git init
Create a new repository here

jj config set --user user.name "*<name>***"**
Set your name

jj config set --user user.email "*<email>***"**
Set your email

CHANGES

jj st
Show the working-copy change

jj diff
Diff of the current change

jj diff -r *<rev>*
Diff of another change

jj show *<rev>*
Message and diff of a change

jj describe -m "*<msg>***"**
Set the current change's message

jj describe *<rev>*
Edit another change's message

jj commit -m "*<msg>***"**
Describe @ and start a new one

jj new
Start a new empty change on @

jj new *<rev>*
Start a new change on <rev>

jj new -m "*<msg>***"**
New change with a message

jj edit *<rev>*
Make <rev> the working copy

CHANGES (cont.)

jj next / jj prev
Step to child or parent

jj restore *<path>*
Discard changes to a file

HISTORY

jj log
Show the revision graph

jj log -r *<revset>*
Log selected revisions

jj log -p
Log with patches

jj file annotate *<path>*
Blame a file

jj file show -r *<rev>* *<path>*
Print a file at a revision

REWRITING

jj squash
Move @ into its parent

jj squash --into *<rev>*
Move @ into any ancestor

jj squash -i
Pick which parts to move

jj split
Split @ into two changes

jj absorb
Auto-squash edits into ancestors

REWRITING (cont.)

jj rebase -s *<rev>* **-o** *<dest>*
Move a change and its descendants

jj rebase -r *<rev>* **-o** *<dest>*
Move only one change

jj rebase -b *<rev>* **-o** *<dest>*
Move a whole branch

jj abandon *<rev>*
Drop a change, keep its children

BOOKMARKS & REMOTES

jj bookmark list
List bookmarks

jj bookmark create *<name>*
Create a bookmark at @

jj bookmark set *<name>* **-r** *<rev>*
Point a bookmark at a revision

jj bookmark delete *<name>*
Delete a bookmark

jj bookmark track *<name>*@*<remote>*
Track a remote bookmark

BOOKMARKS & REMOTES (cont.)

jj git fetch
Fetch from the remote

jj git push
Push changed bookmarks

jj git push -b *<name>*
Push one bookmark

jj git push -c *<rev>*
Push with an auto-named bookmark

jj git remote add *<name>* *<url>*
Add a remote

UNDO & CONFLICTS

jj undo
Undo the last operation

jj redo
Redo an undone operation

jj op log
List past operations

jj op restore *<id>*
Restore the repo to an operation

jj resolve
Resolve conflicts with a merge tool

jj resolve --list
List conflicted files