Julia Fast scientific language

CONCEPTS

> Julia compiles each method on first call, so the first run is slow and later calls are fast. Keep one REPL open.

Generic function name: area
↓ call with args
Dispatch all argument types
↓ first call
Method specialized, compiled
↓ cached
Fast native code reused after

COMMAND LINE

julia
Start the interactive REPL

julia *<file.jl> <args>*
Run a script; args land in ARGS

julia -e '*<expr>***'**
Evaluate an expression and exit

julia --project=*<dir>*
Activate the environment in a folder

julia -t *<n|auto>*
Set the number of threads

julia -i *<file.jl>*
Run a file, then stay in the REPL

REPL

?
Help mode: docs for a name

]
Package mode

;
Shell mode: run a shell command

Backspace
Leave a special mode

Ctrl+D / exit()
Quit Julia

Ctrl+C
Interrupt running code

REPL (cont.)

@time *<expr>*
Time an expression and show allocations

using *<Pkg>*
Load a package's exports

PACKAGES

add *<pkg>*
Add a package to the environment

activate *<dir>*
Switch to the environment in a folder

BASICS

println("x = $x")
Print with interpolation

for i in 1:10 ... end
Loop over a range

function f(x, y=2; k=1) ... end
Function with default and keyword args

ARRAYS

[1, 2, 3]
Vector literal

[1 2; 3 4]
Matrix literal

A[i, j]
Element at row i, column j

push!(v, x)
Append to a vector

[f(x) for x in v if *<cond>***]**
Comprehension

f.(v)
Broadcast f over elements

TYPES & DISPATCH

struct P x::Float64; y::Float64 end
Immutable composite type

area(s::Circle) = pi * s.r^2
Method for one type