k6 Load testing

CONCEPTS

Scripts are JavaScript, but k6 runs them in its own Go runtime: no Node.js APIs, no npm install.

init imports, options
↓ once
setup() returns data
↓ data
default() loops per VU
↓ data
teardown() cleanup

Failed checks do not change the exit code. Add a threshold on the checks metric to fail the run.

RUNNING

k6 new [<*file*>**]**
Scaffold a script

k6 run <*script*>
Run a script locally

--vus <*n*> **/ -u** <*n*>
Concurrent virtual users

--duration <*time*> **/ -d** <*time*>
Total run time, e.g. 3m

--iterations <*n*> **/ -i** <*n*>
Total iterations across VUs

--stage <*time*>**:**<*target*>
Ramp VUs, repeatable (-s)

VARIABLES AND TAGS

-e <*NAME*>**=**<*value*> **/ --env** <*NAME*>**=**<*value*>
Set a variable in __ENV

--tag <*name*>**=**<*value*>
Tag every metric of the run

OUTPUT AND SUMMARY

--out json=<*file*> **/ -o json=**<*file*>
Write every metric point as JSON

DEBUGGING

--http-debug
Log HTTP requests and responses

--http-debug=full
Include request and response bodies

SCRIPT OPTIONS

options block

```
export const options = {
  vus: 10,
  duration: '30s',
};
```

Stages

```
stages: [
  { duration: '30s', target: 20 },
  { duration: '1m', target: 20 },
  { duration: '10s', target: 0 },
],
```

Thresholds

```
thresholds: {
  http_req_duration: ['p(95)<200'],
  http_req_failed: ['rate<0.01'],
  checks: ['rate>0.99'],
},
```

Scenario

```
scenarios: {
  api: {
    executor: 'constant-arrival-rate',
    rate: 20, timeUnit: '1s',
    duration: '1m',
    preAllocatedVUs: 10, maxVUs: 50,
  },
},
```

SCRIPT API

Minimal test

```
import http from 'k6/http';
import { check, sleep } from 'k6';

export default function () {
  const res = http.get('https://test.k6.
io/');
  check(res, { 'status is 200': (r) ⇒
r.status ≡≡ 200 });
  sleep(1);
}
```

check(<*val*>**, { **<*name*>**: **<*fn*>** })**
Assert without stopping the test

sleep(<*seconds*>**)**
Pause the VU between iterations

http.get(<*url*>**)**
GET request

http.post(<*url*>**, **<*body*>**, **<*params*>**)**
POST request

__ENV.<*NAME*>
Read a variable set with -e