kubeconform Manifest schema validator

CONCEPTS

kubeconform checks manifests offline against JSON schemas; it never talks to a cluster, so admission rules and server-side defaults are not tested.

Manifests files, dirs, stdin
↓ parse
Schema lookup kind + apiVersion
↓ validate
Result valid / invalid / skipped

A kind with no schema is an error by default; use -ignore-missing-schemas or -skip, or add a CRD schema location.

Exit code is 0 when all resources pass and 1 when any is invalid or errors.

RUNNING

kubeconform *<file>*
Validate one manifest

kubeconform *<dir>* *<file>*
Validate several paths at once

kubeconform -
Read manifests from stdin

kubeconform -summary *<dir>*
Print totals at the end

kubeconform -verbose *<dir>*
Show valid resources too

kubeconform -exit-on-error *<dir>*
Stop at the first failure

kubeconform -ignore-filename-pattern '*<regex>*' *<dir>*
Skip matching paths

kubeconform -n 16 *<dir>*
Use more parallel workers

kubeconform -v
Print the version

kubeconform -h
Show all flags

STRICTNESS AND VERSIONS

kubeconform -strict *<dir>*
Fail on unknown or duplicate keys

STRICTNESS AND VERSIONS (cont.)

kubeconform -kubernetes-version 1.30.0 *<dir>*
Validate against that Kubernetes version

kubeconform -ignore-missing-schemas *<dir>*
Skip kinds without a schema

kubeconform -skip *<kind>*,*<kind>* *<dir>*
Ignore kinds, all API versions

kubeconform -skip v1/*<Kind>* *<dir>*
Ignore one group/version of a kind

SCHEMAS AND CRDS

kubeconform -schema-location default *<dir>*
Use the built-in schema source

kubeconform -schema-location '*<url-or-path-template>*' *<dir>*
Add a custom schema location

kubeconform -cache *<dir>* *<manifests>*
Cache downloaded schemas on disk

Template variables for -schema-location

Variable	Expand to
`{{.ResourceKind}}`	Kind of the resource
`{{.ResourceAPIVersion}}`	Version part of apiVersion
`{{.Group}}`	API group
`{{.NormalizedKubernetesVersion}}`	Version with a v prefix
`{{.StrictSuffix}}`	-strict when -strict is set
`{{.KindSuffix}}`	Group and version suffix

SCHEMAS AND CRDS (cont.)

Repeat -schema-location to try several sources in order; keep 'default' first so built-in kinds still resolve.

OUTPUT

kubeconform -output pretty *<dir>*
Coloured, human-readable output

kubeconform -output json *<dir>*
Machine-readable result

kubeconform -output junit *<dir>*
JUnit XML for CI reports

kubeconform -output tap *<dir>*
TAP format

kubeconform -output text *<dir>*
Plain text, the default

-summary is ignored with junit output, and -verbose with tap and junit.

RECIPES

Validate a Helm chart

```
helm template <release> <chart> -f values.yaml \
  | kubeconform -strict -summary -kubernetes-version 1.30.0 -
```

Validate a kustomize overlay

```
kustomize build overlays/prod \
  | kubeconform -strict -ignore-missing-schemas -summary -
```

Include CRDs from the Datree catalog

```
kubeconform -strict -summary -schema-location default \
  -schema-location 'https://raw.githubusercontent.com/datreeio/CRDs-catalog/main/{{.Group}}/{{.ResourceKind}}_{{.ResourceAPIVersion}}.json' \
  manifests/
```

CI check with a schema cache

```
mkdir -p /tmp/schemas
kubeconform -cache /tmp/schemas -n 8 -output junit manifests/ > report.xml
```